



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MTLW Manual Top Drive Low Profile Uniform Case Sealer



At a Glance

- Seals cartons as short as 0.5 inch high
- Air-driven brush tucks leading and trailing tape tabs that hang over the bottom of carton
- Accepts 2 inch or 3 inch pop-out BestPack high-speed tape heads
- Up to 40 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Tall Unstable Cases with a 4-Belt Drive Taper

The BestPack MTLW semi-automatic adjustable case sealers are engineered for economical, effective operator-fed closure applications. The MTLW's air-driven brush tucks the leading and trailing tabs that hang over the bottom of the carton. This brush facilitates top sealing of cartons from a minimum height of 0.5" high, three inches lower than the MTD's minimum height of 3.5".

All BestPack case tapers are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

4-belt drive system (2 top and 2 bottom) with idler rollers behind the 1-piece die molded belts that also includes V-belt guide.

Air-driven bottom brush that allows for low top seal down to 0.5" in height.

Top and bottom tape head included for top and bottom seal down to 3.5" in height.

Accepts 2" or 3" pop-out BestPack high-speed tape heads.

Upper side compression unit.

Individually adjustable side width guide rails.

Height adjustment handle can be mounted on either side of the carton sealer.

Electrical on/off box can be mounted on either side of the sealer (left side is standard).

Adjustable bed height from 20.5" to 30.0".

Tape roll lengths: 1000 yd and 1500 yd.
 UL approved electrical parts.

Options

Spare parts kit
 High-speed motor upgrade (up to 125 feet per minute)
 Infeed/exit conveyor with L-bracket stabilizer
 Heavy-duty dual locking casters
 Interlock safety gates
 Food grade 304 stainless steel
 Spare tape head
 Low or no tape sensor

Power & Air

Power: 110 Volts, 60 Hz
 Air: 60-75 psi, 2-3 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MTLW22-2 2" Tape Head	46.1"L 33.5"W 55.5"H	6.0" - ∞"	8.2" - 19.7"	0.5" - 20.3"	20.5" - 30.0"	Up to 40	388 lbs
MTLW22-3 3" Tape Head	46.1"L 33.5"W 55.5"H	6.0" - ∞"	8.2" - 19.7"	0.5" - 20.3"	20.5" - 30.0"	Up to 40	388 lbs
MTLW32-2 2" Tape Head	46.1"L 43.0"W 55.5"H	6.0" - ∞"	8.2" - 30.0"	0.5" - 20.3"	20.5" - 30.0"	Up to 40	416 lbs
MTLW32-3 3" Tape Head	46.1"L 43.0"W 55.5"H	6.0" - ∞"	8.2" - 30.0"	0.5" - 20.3"	20.5" - 30.0"	Up to 40	416 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.