



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack CSD Fully-Auto Servo Random Case Sealer



At a Glance

- Fully-automatic random servo case sealer
- Two servo motors provide precision and speed
- 7-inch color HMI
- Heavy-duty 3mm CNC cut and welded frame including upper welded legs
- Up to 20 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Two Servo Motors Provide Precision and Speed

The BestPack CSD is a top-of-the-line fully-automatic carton sealer that utilizes advanced servo motor technology for precise and efficient sealing.

It offers a cost-effective solution for high-speed carton sealing with its exclusive 2" or 3" pop-out pressure-sensitive tape heads and patented tab adjustment design.

The CSD also includes a no-cost low tape no tape feature and remote connectivity for improved troubleshooting and increased production efficiency.

Additionally, the machine has been designed with a lead screw for enhanced accuracy and positional repeatability, resulting in a smoother and quieter linear motion. A major feature of the CSD is its VPN wifi module providing FREE level 1 phone tech support.

The CSD case taper is equipped with DAS system which provides real-time insights on production metrics such as OEE and tape usage.

Features

Soft touch pneumatic system designed to be gentle on cartons

Servo technology in folding and sealing zone

Operator-friendly and easy remote connectivity

Heavy-duty performance for handling cases weighing up to 70 pounds

Automatically adapt and Handle a variety of box sizes without the need for manual adjustments

Precision accuracy with box measurement

Alarm logging and notification
Low tape / no tape monitoring
All-in-one indexer, flap fold and seal
Upstream and downstream conveyor control
Random side belt drive with high-speed motors
Top flap compression for Center Seal
Precision lead screw for servo movement

Options

Stainless steel
Closed carton bypass
Additional safety options

Power & Air

Power: 208 Volts, 60 Hz, 3 ph, 20 Amps
Air: 80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
CSD222L-2H-B4 2" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	4.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222L-2H-AO 2" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	4.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222L-3H-B4 3" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	5.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222L-3H-AO 3" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	5.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222R-2H-B4 2" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	4.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222R-2H-AO 2" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	4.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222R-3H-B4 3" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	5.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs
CSD222R-3H-AO 3" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"	5.0" - 20.0"	4.0" - 20.0"	25.5" - 30.0"	Up to 20	2000 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.