



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack CSEG Fully-Auto Side Drive Random Case Sealer



At a Glance

- Purpose built for egg industry standard carton sizes
- Plastic crate pass-through
- Designed for flexibility and high speed
- 3 independent stations include centering, folding and sealing
- Heavy-duty 2mm CNC cut and welded frame including upper welded legs
- Up to 27 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Built for Egg Industry Standard Cartons

The BestPack CSEG fully-automatic random case sealer is designed for flexibility and high speed. BestPack advanced engineering allows the CSEG to seal cartons and crate pass through at 27 cartons per minute.

The CSEG case taper is purpose built for the egg industry's standard carton sizes: 30, 24, 18, 15, 12, 9, and 5 dozen, as well as for reusable plastic crates.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Soft touch pneumatic system designed to be gentle on cartons

In-line carton closure

Independent 3-stage operation: indexing, flap folding & sealing

Allen-Bradley PLC w/ ethernet capabilities

Indexer with carton centering device

Plastic crate pass-through

High-speed motors for belt speed of 125 feet per minute

Carton height sensors

Tape roll lengths: 1000 yd & 1500 yd

Heavy-duty 2mm CNC cut and welded frame including upper welded legs
 UL approved electrical parts
 Adjustable bed height from 25.5" to 30.0"
 Interlock safety gates
 Capable of interchanging 2", 3", 4", & 6" tape heads
 Low tape / no tape on carton / no cut sensors with malfunction alarm with three-colored light
 Heavy-duty casters
 Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm

Options

Spare parts kit
 Allen Bradley PLC with ethernet capability
 Exit conveyor
 Food grade 304 stainless steel
 Variable frequency drive provides 25-30 cartons per minute
 Variable frequency drive + sidebelt drive upgrade provides 30+ cartons per minute

Power & Air

Power: 110 Volts, 60 Hz
 Air: 85 psi, 12+ scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
CSEG11-2H 2" Tape Head	99.2"L 38.2"W 75.9"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	25.5" - 30.0"	Up to 27	1320 lbs
CSEG11-3H 3" Tape Head	99.2"L 38.2"W 75.9"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	25.5" - 30.0"	Up to 27	1320 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.