



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack CSF Fully-Auto Servo Random Case Sealer



At a Glance

- Fully-automatic random servo case sealer
- One servo motor provides precision and speed
- 7-inch color HMI
- Heavy-duty 3mm CNC cut and welded frame including upper welded legs
- Up to 12 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

One Servo Motor Provides Precision and Speed

The BestPack CSF fully-automatic servo driven random case sealer provides speed and superior fully-automatic technology at an affordable price. The CSF uses one servo motor providing the precision and speed for reliable carton sealing repeatability.

A notable feature of the CSF is its VPN wifi module providing FREE level 1 tech support via a secure private connection. The CSF provides the best fully automatic technology at an affordable price.

The CSF incorporates exclusive 2" or 3" pop-out pressure-sensitive high-speed tape heads with BestPack's patented tab adjustment.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

- Soft touch pneumatic system designed to be gentle on cartons
- Heavy-duty 3mm CNC cut and welded frame including upper welded legs
- 7-inch color human machine interface
- 1 servo motor (folding section)
- Allen-Bradley MicroLogix PLC
- Random side belt drive with high-speed motors
- Floating sealing section

Independent 3-stage operation: centering, flap folding, & sealing
Adjustable bed height from 25.5" - 30.0"
Interlock safety gates
Maintenance free air cylinder
Analog height & width sensors
Interchangeable 2" and 3" BestPack high-speed tape heads
UL approved electrical parts
Upstream and downstream interlock
Low tape / no tape on carton / no cut sensors & alarm with three color
Warning light
Heavy-duty casters
Remote support eWon
Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm
eWon VPN WiFi module: Connect BestPack's free level 1 technical support to the machine through the customers internet using a secure private connection

Options

Spare parts kit
Food grade 304 stainless steel
Closed carton bypass
Larger carton sizes
Pressure sensitive paper tape application
Left or right justification
208V 3 phase power
CAT3 electrical and air purge valve

Power & Air

Power: 110 Volts, Single ph, 20 Amps
Air: 80 psi, 9 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
CSF222L-2H-AO 2" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"L	4.0" - 20.0"W	4.0" - 20.0"H	25.5" - 30.0"	Up to 12	1800 lbs
CSF222L-3H-AO 3" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"L	5.0" - 20.0"W	4.0" - 20.0"H	25.5" - 30.0"	Up to 12	1800 lbs
CSF222R-2H-AO 2" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"L	4.0" - 20.0"W	4.0" - 20.0"H	25.5" - 30.0"	Up to 12	1800 lbs
CSF222R-3H-AO 3" Tape Head	95.7"L 59.4"W 82.2"H	8.0" - 25.5"L	5.0" - 20.0"W	4.0" - 20.0"H	25.5" - 30.0"	Up to 12	1800 lbs
CSF322L-2H-AO 2" Tape Head	122.0"L 59.4"W 82.2"H	8.0" - 38.5"L	4.0" - 20.0"W	4.0" - 20.0"H	25.5" - 30.0"	Up to 10	2100 lbs
CSF322R-2H-AO 2" Tape Head	122.0"L 59.4"W 82.2"H	8.0" - 38.5"L	4.0" - 20.0"W	4.0" - 20.0"H	25.5" - 30.0"	Up to 10	2100 lbs
CSF333L-2H-AO 2" Tape Head	122.0"L 76.0"W 98.5"H	8.0" - 38.5"L	4.0" - 30.0"W	4.0" - 30.0"H	25.5" - 30.0"	Up to 8	3000 lbs
CSF333R-2H-AO 2" Tape Head	122.0"L 76.0"W 98.5"H	8.0" - 38.5"L	4.0" - 30.0"W	4.0" - 30.0"H	25.5" - 30.0"	Up to 8	3000 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.