



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack CSS Fully-Automatic Servo Side Drive Random Case Sealer



At a Glance

- Fully-auto side belt servo-driven technology
- 3 independent stations include centering, folding and sealing
- Precise positioning at each station
- Up to 30 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fully-Auto Servo-Driven Case Sealing

The BestPack CSS fully-automatic random case sealer featuring servo driven technology provides fast height adjustment, quick width adjustment, and smooth sealing operations.

The CSS design utilizes three independent stations: centering, flap folding, and sealing. The CSS is designed for speed and allows for precise positioning at each station. This machine is capable of a carton output up to 30 cartons per minute.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 3mm CNC cut and welded frame including upper welded legs.

Allen-Bradley HMI.

Allen-Bradley servo.

Allen-Bradley PLC.

Allen-Bradley VFD for side belt high-speed drives.

Floating sealing section.

Independent 3-stage operation: centering, flap folding, and sealing.

Adjustable bed height: 24.5" - 30.0".

Interlock safety gates.

Interchangeable 2" and 3" BestPack high-speed tape heads.

UL approved electrical parts.

Carton pass through without tape.

Low tape / no tape on carton / no cut sensors & alarm with three color warning light.

Heavy duty casters.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Spare parts kit

Food grade 304 stainless steel

Omron PLC

Yaskawa servo motors and drives

Spare tape head

Power & Air

Power: 208 Volts, 3 Ph

Air: 80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
CSS22-2H 2" Tape Head	95.9"L x 50.4"W x 90.3"H	10.0" - 25.5"	7.0" - 20.0"	4.0" - 20.0"	24.5" - 30.0"	Up to 30	2440 lbs
CSS22-3H 3" Tape Head	95.9"L x 50.4"W x 90.3"H	10.0" - 25.5"	7.0" - 20.0"	4.0" - 20.0"	24.5" - 30.0"	Up to 30	2440 lbs
CSS33-4H 4" Tape Head	116.9"L x 60.7"W x 100.4"H	10.0" - 30.0"	7.0" - 30.0"	4.0" - 30.0"	24.5" - 30.0"	Up to 22	3100 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.