



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack CT4E Fully-Auto Four Edge Random Case Sealer



At a Glance

- Automatic four-edge random case sealing
- Eliminate costly hand taping of four outer edges
- Up to 5 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Automatically Applies Tape to Four Edges

The BestPack CT4E fully-automatic case sealer automatically applies pressure sensitive tape to four outer edges of cartons. The CT4E is designed to eliminate costly hand taping of the four outer edges where pilfer-proofing and protection of your product is necessary.

The CT4E edge taper includes a front side entry for a 90 degree directional carton turn before entering into the four edge sealing station.

Features

Heavy-duty 3mm welded frame

Seals all four outside carton edges including all corners

Random width and random height adjustment 90 degree carton turn using front side carton infeed

Top and bottom four belt drive system with 1-piece molded belts and V-belt guide

Includes four 3" BestPack pop-out high-speed tape heads

Low tape / no tape on carton / no cut sensors with malfunction alarm and three-colored light heavy-duty upper assembly four post system

Uses heavy-duty SMC oil-less cushioned air-cylinder

Allen-Bradley PLC Logic

Interlock safety gates where needed

Tape roll lengths: 1,000 yd

Quality UL approved electrical parts

Options

Spare parts kit

Available in either left side infeed or right side infeed (side infeed turns carton 90 degrees for edge seal carton position)

Food grade 304 stainless steel

Power & Air

Power: 110 Volts, 60 Hz

Air: 100 psi, 10+ scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
CT4EL22-3 3" Tape Head	98.43"L 53.15"W 67.32"H	11.81" - 23.62"	9.84" - 23.62"	9.84" - 23.62"	Set at order	Up to 5	1470 lbs
CT4ER22-3 3" Tape Head	98.43"L 53.15"W 67.32"H	11.81" - 23.62"	9.84" - 23.62"	9.84" - 23.62"	Set at order	Up to 5	1470 lbs
CT4ES32-3 3" Tape Head	133.8"L 72.2"W 85.8"H	9.5" - 32.0"	10.0" - 22.0"	5.0" - 20.0"	Set at order	Up to 5	1675 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.