



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack RS-6 6-Inch Random Side Drive Case Sealer



At a Glance

- Semi-automatic random case sealer using 6 inch tape
- Side belt drive
- Seals a wide range of random carton weights and sizes
- Up to 15 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal a Wide Variety of Cartons with 6" Tape

The BestPack RS-6 6-inch semi-automatic random case sealer is incredibly flexible, built for speed, with rugged dependability using 6" wide tape.

With side belt drives, the RS-6 easily seals a wide range of random carton weights and sizes. Able to effectively seal very light to very heavy cartons, RS sealers are workhorses and the most flexible workhorses in BestPack's random carton sealer line.

The RS-6 is perfect for random applications needing extra security, tamper protection, and pilferage prevention. The RS-6 also effectively seals cartons that are overly heavy, over-filled, or otherwise difficult to keep sealed.

Features

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Random side belt drive system with 1-piece molded belts and V-belt guide.

Accepts 6", 4", 3" and 2" pop-out BestPack high-speed tape heads.

Electrical on/off box can be mounted on either side of the carton sealer.

Uses heavy-duty SMC oil-less cushioned air-cylinders.

Adjustable bed height: 20.5" to 30.0".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Upper random mast is tapped and drilled that can be raised (un-bolted, raised and re-bolted) for an extra 4" carton height if needed.

Quality UL approved electrical parts.

Options

Infeed / exit conveyor with L-bracket stabilizer
Heavy-duty dual locking casters
Spare parts kit
High-speed motor upgrade (up to 125 feet per minute)
Interlock safety gates
Food grade 304 stainless steel

Power & Air

Power: 110 Volts, 60 Hz
Air: 80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
RS22-6 2" Tape Head	42.9"L 34.8"W 71.8"H	6.0" - ∞"	8.5" - 21.0"	4.0" - 20.5"	20.5" - 30.0"	Up to 15	475 lbs
RS22-6M 6" Tape Head	42.9"L 34.8"W 71.8"H	6.0" - ∞"	8.5" - 21.0"	4.0" - 20.5"	20.5" - 30.0"	Up to 15	475 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.