



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack RS-S Stainless Random Side Drive Case Sealer



At a Glance

- Stainless steel semi-auto random case sealer for wet environments
- Side belt drive
- Seals a wide range of random carton weights and sizes
- Up to 15 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Random Cartons in Wet Environments

The BestPack RS-S stainless steel semi-automatic random case sealer is built for speed and rugged dependability. Using side belt drives, the RS-S easily seals a wide range of random carton weights and sizes, with masts that allow for an extra 4" of carton height on the upper assembly.

Able to effectively seal very light to very heavy cartons, BestPack RS-S sealers are used in wet environments. These tapers are built for either splash resistant or wash-down applications.

All BestPack stainless steel units are built with food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 2mm food grade 304 stainless steel welded frame including upper welded legs.

Random side belt drive system with 1-piece molded belts and V-belt guide.

Accepts 2" and 3" pop-out BestPack high-speed food grade 304 stainless steel tape heads.

Electrical on/off box is mounted on the left side.

Heavy-duty maintenance free oil-less air cylinder.

Adjustable bed height: 20.5" to 30.0".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Upper random mast is tapped and drilled that can be raised (un-bolted, raised and re-bolted) for an extra 4" carton height if needed.

Quality UL approved electrical parts.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Food grade 304 stainless steel infeed/exit conveyor w/ L-bracket stabilizer

Food grade 304 stainless steel heavy-duty dual locking casters

Spare parts kit

High-speed motor upgrade (up to 125 feet per minute)

Aluminum frame interlock safety gates

Spare tape head

Power & Air

Power: 110 Volts, 60 Hz

Air: 80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
RS22-2S 2" Tape Head	42.9"L 34.8"W 71.8"H	6.0" - ∞"	4.25" - 20.0"	4.0" - 21.0"	20.5" - 30.0"	Up to 15	432 lbs
RS22-3S 3" Tape Head	42.9"L 34.8"W 71.8"H	6.0" - ∞"	5.25" - 20.0"	4.0" - 21.0"	20.5" - 30.0"	Up to 15	432 lbs
RS23-2S 2" Tape Head	42.9"L 34.8"W 76.0"H	6.0" - ∞"	4.5" - 21.6"	4.0" - 30.0"	20.5" - 30.0"	Up to 12	464 lbs
RS23-3S 3" Tape Head	42.9"L 34.8"W 76.0"H	6.0" - ∞"	5.5" - 21.6"	4.0" - 30.0"	20.5" - 30.0"	Up to 12	464 lbs
RS32-2S 2" Tape Head	42.9"L 44.2"W 71.8"H	6.0" - ∞"	4.5" - 30.0"	4.0" - 21.0"	20.5" - 30.0"	Up to 12	487 lbs
RS32-3S 3" Tape Head	42.9"L 44.2"W 71.8"H	6.0" - ∞"	5.5" - 30.0"	4.0" - 21.0"	20.5" - 30.0"	Up to 12	487 lbs
RS33-3S 3" Tape Head	42.9"L 44.2"W 76.0"H	6.0" - ∞"	5.5" - 30.0"	4.0" - 30.0"	20.5" - 30.0"	Up to 12	632 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.