



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack RS Random Side Drive Case Sealer



At a Glance

- Semi-automatic random case sealer
- Side belt drive
- Seals a wide range of random carton weights and sizes
- Up to 15 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Side Belts Seal a Wide Variety of Cartons

The BestPack RS semi-automatic random case sealer is built for speed and rugged dependability. Using side belt drives, the RS easily seals a wide range of random carton weights and sizes, with masts that allow for an extra 4" of carton height on the upper assembly.

Able to effectively seal very light to very heavy cartons, BestPack's RS sealer is a workhorse and the most flexible unit in BestPack's random carton sealer product line.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Adjustable bed height: 20.5" - 30".

2 side belt drive.

Extra 4" carton height adjustment available on upper assembly.

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Quality UL approved electrical parts.

Capable of interchanging 2" or 3" tape heads.

Electrical on/off box can be mounted on either side of the carton sealer.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Spare parts kit
 High-speed motor upgrade (Up to 125 feet per minute)
 Locking heavy-duty casters
 Interlock safety gates
 Low tape / no tape sensor
 Infeed / exit conveyor with L-bracket stabilizer
 Food grade 304 stainless steel
 Spare tape head

Power & Air

Power: 110 Volts, 60 Hz

Air: 55-80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
RS22-2 2" Tape Head	42.9"L x 34.8"W x 71.8"H	6.0" - ∞"	4.25" - 20.0"	4.0" - 21.0"	20.5" - 30.0"	Up to 15	410 lbs
RS22-3 3" Tape Head	42.9"L x 34.8"W x 71.8"H	6.0" - ∞"	5.25" - 21.0"	4.0" - 21.0"	20.5" - 30.0"	Up to 15	410 lbs
RS23-2 2" Tape Head	42.9"L x 34.8"W x 76.0"H	6.0" - ∞"	4.5" - 20.0"	4.0" - 30.0"	20.5" - 30.0"	Up to 12	440 lbs
RS23-3 3" Tape Head	42.9"L x 34.8"W x 76.0"H	6.0" - ∞"	5.5" - 21.0"	4.0" - 30.0"	20.5" - 30.0"	Up to 12	440 lbs
RS32-2 2" Tape Head	42.9"L x 44.2"W x 71.8"H	6.0" - ∞"	4.5" - 30.0"	4.0" - 20.5"	20.5" - 30.0"	Up to 12	462 lbs
RS32-3 3" Tape Head	42.9"L x 44.2"W x 71.8"H	6.0" - ∞"	5.5" - 30.0"	4.0" - 20.5"	20.5" - 30.0"	Up to 12	462 lbs
RS33-3 3" Tape Head	42.9"L x 44.2"W x 76.0"H	6.0" - ∞"	5.5" - 30.0"	4.0" - 30.0"	20.5" - 30.0"	Up to 12	600 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.