



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack RSBFT Random Side Drive Flap Folder



At a Glance

- Quickly tape random carton bottoms
- Side belt drive
- T rail with bottom major flap folding horns
- Up to 10 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Side Belts Seal a Wide Variety of Cartons

The BestPack RSBFT random operator-fed, bottom carton sealer is designed to reduce the time required to fold and seal the bottom flaps of a carton.

This RSBFT bottom-only taper is perfect for when carton-forming volume has become too large to manually form and tape cartons, but not large enough to justify a fully-automatic carton erector/sealer.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

2 side belt drive.

Random bottom flap folder.

T rail with bottom major flap folding horns.

Adjustable Bed Height from: 23.5" to 30.0".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Quality UL approved electrical parts.

Capable of interchanging 2" or 3" tape heads.

Heavy-duty maintenance-free oil-less air cylinder.

High-speed motors.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Food grade 304 stainless steel
Spare parts kit
Exit conveyors
Locking casters with support brackets
Spare tape head

Power & Air

Power: 110 Volts, 60 Hz
Air: 55-80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
RSBFT20-2H 2" Tape Head	95.9"L x 35.5"W x 29.4"H	7.8" - 23.6"	7.8" - 19.6"	4.0" - ∞"	23.5" - 30.0"	Up to 10	350 lbs
RSBFT20-3H 3" Tape Head	95.9"L x 35.5"W x 29.4"H	7.8" - 23.6"	7.8" - 19.6"	4.0" - ∞"	23.5" - 30.0"	Up to 10	350 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.