



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# BestPack RSL-6 6-Inch Random Side Drive Low Profile Case Sealer



## At a Glance

- Random case sealer for very low profile cartons
- Seals with 6 inch tape
- Seals a wide range of random carton weights and sizes
- Up to 12 cases per minute

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Side Belts Seal a Wide Variety of Cartons

The BestPack RSL-6 semi-automatic random case sealer is the 6" version of the low-profile RSL machine. Built for speed and durability, the RSL's low profile feature allows for the effective sealing of cartons at a minimum height of 2.5".

The RSL-6 case taper is perfect for random applications needing extra security, tamper protection, and pilferage prevention, and also effectively seals cartons that are overly heavy, over-filled, or otherwise difficult to keep sealed.

## Features

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Random side belt drive system with 1-piece molded belts and V-belt guide.

Accepts 6", 4", 3" and 2" pop-out BestPack high-speed tape heads.

Seals cartons as low as 2.5" in height.

Electrical on/off box can be mounted on either side of the carton sealer.

Uses heavy-duty SMC oil-less cushioned air-cylinders.

Upper random mast is tapped and drilled that can be raised (un-bolted, raised and re-bolted) for an extra 4" carton height if needed.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Adjustable bed height from 20.25" to 30.75".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.  
Quality UL approved electrical parts.

## Options

Infeed / exit conveyor with L-bracket stabilizer  
Heavy-duty dual locking casters  
Spare parts kit  
High-speed motor upgrade (up to 125 feet per minute)  
Interlock safety gates  
Food grade 304 stainless steel  
Spare tape head

## Power & Air

Power: 110 Volts, 60 Hz  
Air: 80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

## Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Case per Minute	Shipping Weight
RQ22-6 6" Tape Head	57.3"L 34.6"W 57.5"H	6.0" - ∞"	9.7" - 21.6"	2.5" - 20.5"	20.5" - 30.0"	Up to 12	450 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.