



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack RSL Random Side Drive Low Profile Case Sealer



At a Glance

- Semi-automatic random case sealer for very low profile cartons
- Side belt drive
- Seals a wide range of random carton weights and sizes
- Up to 12 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Random Very Low Profile Cartons

The BestPack RSL semi-automatic random case sealers are designed to seal very low profile cartons in addition to a wide range of a random cartons. Built for speed and durability, the RSL's low profile feature allows for the effective sealing of cartons with a height as low as 2.5". The RSL is capable of sealing cartons up to 20.5" tall as well.

Features

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Random side belt drive system with 1-piece molded belts and V-belt guide.

Seals cartons as low as 2.5" in height.

Electrical on/off box can also be easily mounted on either side of the sealer (left side is standard).

Uses heavy-duty SMC oil-less cushioned air-cylinders.

Upper random mast is tapped and drilled that can be raised (un-bolted, raised and re-bolted) for an extra 4" carton height if needed.

Adjustable bed height: 20.5" - 30".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Quality UL approved electrical parts.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Infeed / exit conveyor with L-bracket stabilizer

Heavy-duty dual locking casters
 Spare parts kit
 High-speed motor upgrade (up to 125 feet per minute)
 Interlock safety gates
 Food grade 304 stainless steel
 Spare tape head

Power & Air

Power: 110 Volts, 60 Hz
 Air: 55-80 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Case per Minute	Shipping Weight
RSL22-2 2" Tape Head	60.4"L x 34.8"W x 71.8"H	6.0" - ∞"	5.7" - 21.0"	2.5" - 20.5"	20.5" - 30.0"	Up to 12	450 lbs
RSL22-3 3" Tape Head	60.4"L x 34.8"W x 71.8"H	6.0" - ∞"	6.7" - 21.0"	2.5" - 20.5"	20.5" - 30.0"	Up to 12	450 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.