



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey BB-2 Bottom Belt Case Sealer



At a Glance

- Top and bottom tape heads are interchangeable and tip back for easy threading
- Industrial strength drive belts move boxes consistently through the taper
- Adjustable side rails and tape head offer fast and easy case changes
- Top and bottom tapeheads are identical and can be removed instantly without tools

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Cost-Effective Case Sealing

The Eastey BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes at a cost-effective price.

Eastey's BB-2 case taper is a cost-effective top and bottom case taper designed for large run case sealing. BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes.

The BB-2 offers the durability, versatility and reliability that you have come to rely on from Eastey. The system's unique and simple design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum and providing fast and efficient alternatives to hand taping.

The Eastey BB-2 offers fast and easy case changes with adjustable side rails and flexibility ranging from 5" to infinite box length. The BB-2 is also able to seal cases ranging from 6" to 21" in width, as well as 4" to 20.5" in depth. Adjustments can be made on the fly with easy hand tighten knobs on a single mast design. The BB-2's open design is also perfect for integration with ink jet printers where coding is required on boxes.

Case Taping as Easy as 1-2-3

The BB-2 top and bottom tape heads are interchangeable and tip back for easy threading. No air is required to run the BB-2 taping system so it can be placed anywhere in the factory. A safe single mast allows clear access to all components and adjusts for a variety of case sizes. The use of Eastey's BB-2

case taping machine can be learned in minutes, avoiding breaks in production and downtime, saving your company money and increasing your ROI.

Industrial Strength Operation

A single drive motor and aggressive industrial strength drive belts make BB-2 a workhorse that will stand up to your toughest challenges. Each case taping machine is made from 12 gauge steel that withstands even the most rugged applications. A powder coated exterior protects the machine from abusive conditions and guarantees years of use.

Features

- Plug-in and go operation
- Powder coated 12 gauge steel
- Interchangeable top and bottom tape cartridges
- Adjustable side rails
- Safe single mast design
- No air required
- Low maintenance
- Simple integration with ink jet printers
- Includes 2 pack tables and casters

Case Sizes

Minimum: 5"L x 6"W x 4"D
Maximum: Infinite L x 21"W x 20.5"D

Options

- 3" tape head accepts 3" wide tape rolls
- Top squeezers allows for operation with variable speed conveyors

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Sealer Type	Bottom belt, top and bottom case sealer
Machinery Makeup	Industrial strength 12 gauge steel, powdered coated for durability
Belt Speed	60 feet/per minute
Tape Speed	30 cases/per minute, depending on box size and operator efficiency
Casters	Rugged wheels for transportation within plant
Front & Rear Packing	Solid tables bolt before and/or after taping system to allow for case packing
Adjustable Side Rails	Palm grip knobs offer quick and simple adjustments
Height Adjustment	Standard adjustable legs for 22.25" to 35.25" conveyor heights
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
Air Requirements	None
Electrical Requirements	110 VAC, 60Hz, 6A

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.