



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey SB-2EX Easy Packer Side Belt Case Sealer



At a Glance

- Flap closing bars plow and assist in flap closing prior to being sealed
- Industrial strength drive belts move boxes consistently through the taper
- Adjustable side rails and tape head offer fast and easy case changes
- Top and bottom tapeheads are identical and can be removed instantly without tools

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact Case Erecting, Packing and Sealing

The Eastey Easy Packer is designed to streamline manual case packing with or without an anvil pack station, extended side rails, and flap closing bars to assist with the packing and sealing process.

The side belt driven Easy Packer is designed for compact, packing and sealing. The durable design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum. The Easy Packer provides a fast and cost efficient alternative to hand taping.

Designed with the customer in mind, the Easy Packer is supplied with extended side rails, flap closing bars, and a 48" anvil packing station (not shown) to assist with the packing and sealing process. Operation is simple: open the case and manually fold the bottom front and back minor flaps and place case on the anvil to be filled. Once filled, the operator pushes down and holds the top trailing minor flap while the box enters the machine to be sealed.

Easy Packer offers fast and easy case changes with adjustable side rails and flexibility for boxes 5" in length and greater. Adjustments can be made on the fly with easy hand tighten knobs and cranks. Easy Packer utilizes Eastey's Easy-Taper Quick-Load top and bottom tape cartridges and will seal boxes as narrow as 4.0" wide and as low as 4.0" tall.

Less Down Time

Easy Packer offers fast and easy case changes with adjustable side rails and flexibility for boxes 5" in

length and greater. Adjustments can be made on the fly with easy hand tighten knobs and cranks. Easy Packer utilizes Eastey's Easy-Taper Quick-Load top and bottom tape cartridges and will seal boxes as narrow as 4.0" wide and as low as 4.0" tall.

Industrial Quality

CE approved dual drive motors, aggressive industrial strength side belts and roller tables make Easy Packer a workhorse. Each machine is made from 12 gauge steel and will withstand the most rugged applications. The powder coated exterior protects the machine from abusive conditions and guarantees years of use.

Convenience

These machines accept 2" wide pressure-sensitive tape as a standard, or can be ordered with 3" tape heads. The use of Eastey's Easy Packer case taping machine can be learned in minutes, avoiding breaks in production and downtime, saving your company money and increasing your ROI.

Features

- Utilizes Eastey's Easy-Taper tapehead
- Anvil packing station for easy case packing
- Plug-in and go operation
- Powder coated 12 gauge steel
- Top and bottom tape cartridges
- Industrial strength side belts
- Adjustable leg extensions
- Fast and easy box size changes
- Low maintenance
- Accommodates wide case range
- Casters for transportation within plant

Case Sizes

Minimum: 5"L x 4"W x 4"D
Maximum: Infinite L x 19.5"W x 19.5"D

Options

- 3" tape head accepts 3" wide tape rolls
- Front packing roller table before taping system replaces anvil packing station
- Rear table roller after taping system to allow for case movement

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Sealer Type	Uniform side belt, top and bottom case sealer
Machinery Makeup	Industrial strength 12 gauge steel, powdered coated for durability
Belt Speed	75 feet/per minute
Tape Speed	20 cases/per minute, depending on box size and operator efficiency
Height Adjustment	Standard adjustable legs for 20" to 32.3" conveyor heights
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
Air Requirements	None
Electrical Requirements	110 VAC, 60Hz, 4.0A
Agency Approvals	CE Certification

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.