



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Eastey SB-2EX Automatic Uniform Case Taper



## At a Glance

- Automatically closes all four flaps and seals the top and bottom of cases
- Automatically meters cartons with a photo eye controlled gating system
- Seals up to 20 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this Eastey case taper!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Automatic Case Closing and Sealing

The Eastey SB-2EX Auto is a semi-automatic uniform side belt case taper designed to close all four top case flaps and seal the top and bottom of each case. The adjustable plow system provides the utmost flexibility for varying types of carton sealing applications and provides a great alternative to hand taping. The SB-2EX Auto will seal up to 20 cases per minute.

The SB-2EX Auto will accept cartons from a powered conveyor and will automatically close the top carton flaps. A rugged stainless steel plow folds down the front panel, while a rear kicker folds down the trailing minor flap prior to the major flaps being folded. The SB-2EX Auto automatically meters cartons with a photo eye controlled gating system. Top squeezing rollers help keep the major flaps together while keeping the carton square prior to tape application.

The Eastey SB-2EX Auto offers fast and easy case changes and flexibility for boxes 5" to 24" in length. The adjustable hand cranks can be moved to either side of the machine and allow for quick carton change over. This feature allows you to locate either side against a wall, while being able to maintain control of the adjustments from the opposite side. SB-2EX Auto utilizes Eastey's EX Quick-Load top and bottom tape cartridges and will seal boxes as narrow as 4.5" wide and as low as 4.5" tall.

## Affordable Functionality

Top and bottom tape heads lift out for easy threading. The Eastey SB-2EX Auto accepts 2" wide pressure-sensitive tape as a standard, or can be ordered with 3" tape heads. The use of Eastey's SB-2EX Auto case taping machine can be learned quickly, avoiding breaks in production and downtime, saving your company money and increasing your ROI.

## Quality Construction

The Eastey SB-2EX Auto features CE approved dual drive motors and aggressive industrial strength side drive belts. Each case taping machine is made from 12 gauge steel that withstands even the most rugged applications. A powder coated exterior protects the machine from abusive conditions and guarantees years of use.

## Features

- Utilizes Eastey's EX tapehead
- Plug-In and go operation
- Powder coated 12 gauge steel
- Adjustable side guides
- Industrial strength side belts
- Adjustable leg extensions
- Fast and easy box size changes
- Low maintenance
- Accommodates wide case range
- Casters for transportation within plant

## Case Sizes

Minimum: 5"L x 4.5"W x 4.5"D

Maximum: 24"L x 19.5"W x 19.5"D

## Options

- 3" tape head accepts 3" wide tape rolls
- Front packing roller table before taping system replaces anvil packing station
- Rear table roller after taping system to allow for case movement

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

## Specifications

Sealer Type	Fully automatic uniform side belt, top and bottom case sealer
Machinery Makeup	Industrial strength 12 gauge steel, powdered coated for durability
Belt Speed	75 feet/per minute
Tape Speed	20 cases/per minute, depending on box size and operator efficiency
Height Adjustment	Standard adjustable legs for 27" to 34.6" conveyor heights
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
Air Requirements	85 psi
Electrical Requirements	110 VAC, 60Hz, 6A
Agency Approvals	CE Certification

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.