



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Easteey SB-2EX-RAN Random Side Belt Case Taper



At a Glance

- Automatically adjusts the side rails and tape head height for different size cases
- Ideal for void-fill cases where the packaged product does not support the box
- Dual 1/4 hp drive motors, aggressive industrial strength drive belts

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this Easteey case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Random Case Sealing

The Easteey SB-2EX Random allows users to run a variety of case sizes without having to manually adjust for each box. This taper automatically adjusts the side rails and tape head height for different size cases.

Easteey's SB-2EX Random unique and simple design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum and providing fast and efficient alternatives to hand taping.

The SB-2EX Random side belts are great for heavy weight, narrow, or small boxes. It is ideal for void-fill random cases where the packaged product does not support the box. The SB-2EX Random is designed to handle boxes that most other case tapers can't.

The Easteey SB-2EX Random utilizes easy to load top and bottom tape cartridges and will seal boxes as narrow as 4.5" wide and as low as 4.5" tall. Side rail and tape head height adjustments are made automatically on the fly as soon as the case is presented to the automatic sensors. In addition, the SB-2EX Random comes equipped with a memory function that adjusts to the maximum box depth. This eliminates full travel of the tape head and reduces wear on the machine.

Industrial Strength Operation

Dual 1/4 drive motors, aggressive industrial strength drive belts, and roller tables make SB-2EX Random a workhorse that will stand up to your toughest challenges. Each case taping machine is made from 12 gauge steel that will withstand even the most rugged applications. A powder coated exterior protects the machine from abusive conditions and guarantees years of use.

Case Taping Made Easy

The SB-2EX Random is designed and built with the customer in mind. Top and bottom tape cartridges are interchangeable and designed for easy tape threading. These machines accept 2" wide pressure-sensitive tape as a standard, or can be converted in the field with 3" tape heads for wider case taping applications. Operators can learn to use Eastey's SB-2EX Random case taping machine in minutes, avoiding breaks in production and downtime, saving your company money and increasing your ROI.

Features

- Box depth memory function
- Plug-in and go operation
- Accommodates wide box sizes
- Industrial strength side belts
- Interchangeable top and bottom tape cartridges
- Adjustable leg extensions
- Casters for transportation within plant
- Emergency stop button
- Reset button
- Powder coated 12 gauge steel
- Low maintenance

Case Sizes

Minimum: 5"L x 4.5"W x 4.5"D
Maximum: Infinite L x 23"W x 23"D

Options

- 3" tape head accepts 3" wide tape rolls
- Full plexiglass safety enclosure walls for operator safety
- Front and rear table bolt on before or after taping system to allow for case packing and movement

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Sealer Type	Random side belt, top and bottom case sealer
Machinery Makeup	Industrial strength 12 gauge steel, powdered coated for durability
Belt Speed	75 feet/per minute
Tape Speed	15 to 20 cases/per minute, depending on box size and operator efficiency
Height Adjustment	Standard adjustable legs for 21.2" to 34.6" conveyor heights
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
Drive Motor	Two (2) 1/4HP drive motors
Electrical Requirements	110 VAC, 60Hz, 4.0A
Agency Approvals	CE Certification

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.