



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Eastey SB-2EX Side Belt Case Sealer



At a Glance

- Designed for light or heavy weight, narrow or small boxes
- Ideal for void-fill cases where the packaged product does not support the box
- Dual 1/4 hp drive motors, aggressive industrial strength drive belts

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Wide Case Size and Weight Range

The Eastey SB-2EX side belt tapers are great for light or heavy weight, narrow or small boxes. It is ideal for void-fill cases where the packaged product does not support the box.

Eastey's SB-2EX Case Taper offers the quality that you have come to rely on from Eastey. The system's unique and simple design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum and providing fast and efficient alternatives to hand taping.

The SB-2EX's side belts are great for light or heavy weight, narrow or small boxes. It is ideal for void-fill cases where the packaged product does not support the box.

Dual 1/4 hp drive motors, aggressive industrial strength drive belts, and roller tables make SB-2EX a workhorse that will stand up to your toughest challenges. Each case taping machine is made from 12 gauge steel that will withstand even the most rugged applications. A powder coated exterior protects the machine from abusive conditions and guarantees years of use. Best of all, the SB-2EX is CE certified, so users can be confident it will consistently provide reliable, high quality case sealing.

Case Taping Made Easy

The SB-2EX is designed and built with the customer in mind. Top and bottom tape cartridges are interchangeable and designed for easy tape threading. These machines accept 2" wide pressure-sensitive tape as a standard, or can be converted in the field with 3" tape heads for wider case taping applications. Operators can learn to use Eastey's SB-2EX case taping machine in minutes, avoiding breaks in

production and downtime, saving your company money and increasing your ROI.

Features

- Plug-in and go operation
- Fast and easy box size changes
- Industrial strength side belts
- Interchangeable top and bottom tape cartridges
- Emergency stop button
- Adjustable leg extensions
- Casters for transportation within plant
- Front and rear pack tables to allow for case packing
- Top squeezers push top flaps together for accurate case sealing
- Powder coated 12 gauge steel
- Low maintenance, no air required

Case Sizes

- Minimum: 5"L x 4"W x 4"D
- Maximum: Infinite L x 19.5"W x 19.5"D

Options

- 3" tape head accepts 3" wide tape rolls
- Complete stainless finish to meet specific application requirements

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Sealer Type	Side belt, top and bottom case sealer
Machinery Makeup	Industrial strength 12 gauge steel, powdered coated for durability
Belt Speed	75 feet/per minute
Tape Speed	30 cases/per minute, depending on box size and operator efficiency
Height Adjustment	Standard adjustable legs for 18.1" to 32.3" conveyor heights
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges
Drive Motor	Two (2) 1/4HP drive motors
Electrical Requirements	110 VAC, 60Hz, 4.0A
Agency Approvals	CE Certification

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.