

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com 888-318-0083

Little David LD-16AR Automatic Random Case Sealer



At a Glance

- Automatically and quickly seal a wide range of random case sizes
- Allen Bradley PLC, servo controlled
- Up to 20 case per minute
- Category 3 fully interlocking safety guarding
- 7 gauge bolted and welded steel frame
- Reliable 24/7 operation

Buy your case sealing tape from Pro Pac, and get a discount on this case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Heavy-Duty Fully-Automatic High Speed Random Case Taper

The Little David LD-16AR is a fully-automatic case sealer that's ready to process a random assortment of case sizes at speeds up to 20 cases per minute depending on incoming height variance.

The LD-16AR automatically makes adjustments to match the height and width of each case fed into it by a powered conveyor. Two stage operation accurately measures the case size and preadjusts the top tape head. Cases are sealed on the top and bottom with 2" or 3" tape using the latest CaseLocker 60 tape cartridges.

Features

Fully automatic random top and bottom case sealer Process up to 20 cases per minute depending on incoming height variance Self-centering drive belts Dual mast construction Removable 2" or 3" PST tape cartridges High quality steel structure with powder coat finish Heavy-duty bottom belt drive with horizontally mounted 1/4 HP motor Left to right case flow Interlocking safety gates Built in indexing gate 150 FPM belt speed 22.25" conveyor height adjustable up to 28.25" Fully guarded flap "kicker" device Servo driven, ball screw linear actuator High-precision ultrasonic sensing and linear transducer to detect case height & width Allen Bradley MicroLogix 800 PLC Powered roller infeed section to pre-sense case width & height (case-sizer) 1.9" diameter rollers on 2.5" centers Safety flags at infeed sides of powered infeed section

Quality Sealing

Powered top squeezers to assure major flaps meet in case center Flight bar drive Linear self-centering side rails

Safe

Safety monitoring relay Safety doors automatically shut down machine when opened Safety flags at infeed sides of powered infeed section

Options

Automatic or manual tape selectivity feature allows omission of either or both top and bottom closures Special paints, lacquer, enamel, epoxy, special colors, and stainless steel Spare pressure sensitive tape cartridge Casters Spare parts kit Low tape warning No tape warning

Reliable Performance Warranty

year all components
year warranty for gear reducer and motor
year waranty for tape cartridge
(Moving and wear parts are not included, other restrictions may apply)

Please contact Pro Pac or call 888-318-0083 for your case sealing equipment.

LD-16AR Specifications

Case Range	Length: 10" (254 mm) - 24" (610 mm) Width: 4.5" (114 mm) - 20" (508 mm) Height: 4.5" (114 mm) - 20" (508 mm)
Operating Speed	Continuous belt drive150' per minute (45.72 m/min)
Power	110 volts, 60 cycle, single phase, 20 Amp
Air	6 SCFM @ 80 psi
Machine Dimensions	Width: 110" (279.4 cm) Height: 87.375" (221.9 cm)
Machine Weight	1,175 lbs (680kg) uncrated

Please contact Pro Pac or call 888-318-0083 for your case sealing equipment.