



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David LD-24 Automatic Uniform Case Sealer



At a Glance

- Great, compact, low cost automatic uniform case sealer
- Fast pneumatic case folding
- PLC controlled
- Indexing gate and box jam indicator
- Extensive box range
- Standard top squeezer
- Up to 100ft a minute
- Energy saving mode

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this Little David case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact, High-Performance, Low-Cost Automatic Case Taper

The Little David LD-24 is an industrial-grade high-performance fully automatic case sealer. Designed to meet the case sealing demands with high-volume runs of the same box size. Its compact design is perfect for limited space on the floor and between conveyors.

Pneumatic flap folding and a fully-welded frame makes this case taper one of the most reliable and efficient case sealers available.

Features

- Operating Speed: Up to 100' per minute (30.49 m/min)
- Seals with pressure sensitive tape
- Operator controls and adjustments on both sides of the machine
- Safety panel in folding area
- Standard top squeezer
- Capable of running 2" and 3" tape in same machine
- Fully-welded base frame
- Compact footprint
- Quick change belts
- Pneumatically tensioned belts make them adjustment free

More Features

Pneumatic case folding with dual side rear flap tuckers and positive folding of major flaps
Removable crank handles and graduated adjustments that are scaled for fast and precise changeover
Adjustable height and PLC controls can be integrated into your conveyor system for start and stop control

Energy saving mode

Safety panel in folding area

Indexing gate

Box jam indicator

Options

Casters

Flat exit pack table

Roller exit pack table

CF-5 connection kit

Infeed pack table

Optional threaded rods, casters or leveling pads

Stainless steel main frame, threaded rods, casters, leveling pads

LD-24 Specifications

Case Range	Length: 8" (203 mm) - 24" (610 mm) Width: 6" (152 mm) - 18" (557.2 mm) Height: 4.5" (114 mm) - 18" (557.2 mm)
-------------------	---

Operating Speed	100' per minute (30.49 m/min)
------------------------	-------------------------------

Power	110 volts, 60 cycle, single phase
--------------	-----------------------------------

Air	5 SCFM @ 85 psi
------------	-----------------

Machine Dimensions	Width: 65" (165 cm) Depth: 48" (122 cm) Height: 63" (160 cm)
---------------------------	--

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.