



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Little David LDX-RTB 4.0 Semi-Auto Random Case Sealer



## At a Glance

- Fast! Processes random sized cases with a continuous belt speeds up to 155 feet per minute
- Capable of processing void-filled and overstuffed cases at high speeds
- Same machine runs 2 inch and 3 inch tape
- Easy access to motors, electrics, and belts for quick and easy maintenance and repair

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## High-Performance Case Taper

The Little David LDX-RTB 4.0 is engineered for environments where speed and versatility are critical. The LDX-RTB 4.0 Ultra can process void-filled and over-stuffed cases 30-80% faster than the competition.

With a belt speed of 155 feet-per-minute, head movement technology utilizing a pneumatic top tape cartridge, and machine performance data provided by an Allen-Bradley 850 PLC and HMI display technology, the LDX-RTB 4.0 performs with speed and reliability you can depend on.

## Features

Processes void-filled and over-stuffed cases 30% to 80% faster than the nearest competition.

Increased throughput via industry leading belt speed of 185 feet per minute and patent pending enhanced head movement technology.

Top drive assembly travels on case hardened linear shafts with linear bearings.

Easy access to motors, electrics and belts.

Processes weak, void-filled and over-stuffed cases at high speeds utilizing pneumatic top cartridge.

Motors individually protected from overheating due to excessive loading

## Specifications of LDX-RTB 4.0

Case Range	Length: 6" (152 mm) - infinite Width: 5.5" (139 mm) - 26" (660 mm) Height: 3.5" (89 mm) - 24.5" (622 mm)
Operating Speed	Continuous belt driveStandard: 115' per minute (35.05 m/min)High Speed: 155' per minute (47.25 m/min)
Power Requirements	110 volts, 60 cycle, single phase
Air Requirements	9 SCFM @ 85 psi
Closure Material	Pressure sensitive tape
Weight	570 lbs (258 kg) uncrated

## LDX-RTB 4.0 Model Types

Standard	High speed top and bottom belt drive 115' fpm top and bottom mechanical tape cartridges
Deluxe	High speed top and bottom belt drive PLC / top only pneumatic CAC-61 Mechanical CAC 61 HS bottom mechanical cartridge for void in box
Premium	High speed top and bottom belt drive Top and bottom pneumatic CAC-61 tape cartridges with pass-through feature
Premier	High speed top and bottom belt drive PLC / top only pneumatic CAC-61 Mechanical CAC 61 HS bottom mechanical cartridge for void in box Full interlock guarding

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.