



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Little David LDX-UTB Semi-Auto Uniform Case Sealer



## At a Glance

- Fast! Tapes uniform sizes cases up to 155 feet per minute
- Welded tubular steel construction
- Reinforced critical stress points and lightweight removable access panels
- Easy access motors, electrics and belts
- Movable control station
- Top and bottom interchangeable cartridges

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Super-Fast Semi-Auto Uniform Case Taper

The high speed Little David LDX-UTB is a semi-automatic case sealer designed for processing large runs of the same size box. The LDX-UTB has quick manual adjustments to the top drive (for the height of the box) and side rails (for the width of the box). Cases are top and bottom sealed with 2" or 3" tape using the latest CaseLocker 60 tape cartridges.

Constructed of fully welded tubular steel, this top and bottom drive case sealer is optimal for sealing large runs of the same box size at high speeds. Its speed, extensive box range, and instant box changeover with self-centering side rails set it apart from competing machines.

## Features

**High Performance:** This case sealer can process cases 20%-80% faster than the competition, giving you the efficiency you need.

**Industrial Design:** Welded tubular steel construction, reinforced critical stress points and lightweight removable access panels.

**User Friendly:** Self-centering side rails and adjustable top drives, including movable magnetic control station with start/e-stop button and interchangeable top and bottom tape cartridge.

**Simple Maintenance:** Easy access to all the motors, electrics, and belts for quick maintenance or repairs.

**Continuous Belt Drive:** Standard: Up to 115' per minute (35.05 m/min). High Speed: UP to 155' per minute (47.25 m/min.)

# Options

- Casters
- Roller infeed pack table
- Roller exit pack table
- Leg extensions
- High speed
- CF-5 connection kit

## LD-UTB Specifications

Case Range	Length: 6" (152 mm) - infinite Width: 5.5" (139.7 mm) - 26" (660.4 mm) Height: 3.5" (89 mm) - 34.5" (876.3 mm) Optional 2.5" (63.5 mm) minimum box height
Operating Speed	Continuous belt driveStandard: 115' per minute (35.05 m/min)High Speed: 155' per minute (47.25 m/min)
Power	110 volts, 60 cycle, single phase
Air	5 SCFM @ 85 psi
Machine Dimensions	Width: 46.25" (127.7 cm) Depth: 36.625" (93.4 cm) Height: 67.375" (170.9 cm)
Machine Weight	570 lbs (258 kg) uncrated

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.