



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David LDX-UTB Semi-Auto Uniform Case Sealer



At a Glance

- Fast! Tapes uniform sizes cases up to 80% faster than the competition
- Welded tubular steel construction
- Reinforced critical stress points and lightweight removable access panels
- Easy access motors, electrics and belts
- Movable control station
- Top and bottom interchangeable cartridges

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this Little David case taper!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Super-Fast Semi-Auto Uniform Case Taper

The high speed Little David LDX-UTB is a semi-automatic case sealer designed for processing large runs of the same size box. The LDX-UTB has quick manual adjustments to the top drive (for the height of the box) and side rails (for the width of the box). Cases are top and bottom sealed with 2" or 3" tape using the latest CaseLocker 60 tape cartridges.

Constructed of fully welded tubular steel, this top and bottom drive case sealer is optimal for sealing large runs of the same box size at high speeds. Its speed, extensive box range, and instant box changeover with self-centering side rails set it apart from competing machines.

Features

High Performance: This case sealer can process cases 20%-80% faster than the competition, giving you the efficiency you need.

Industrial Design: Welded tubular steel construction, reinforced critical stress points and lightweight removable access panels.

User Friendly: Self-centering side rails and adjustable top drives, including movable magnetic control station with start/e-stop button and interchangeable top and bottom tape cartridge.

Simple Maintenance: Easy access to all the motors, electrics, and belts for quick maintenance or repairs.

Continuous Belt Drive: Standard: Up to 115' per minute (35.05 m/min). High Speed: UP to 155' per minute (47.25 m/min.)

Options

Casters
Roller infeed pack table
Roller exit pack table
Leg extensions
High speed
CF-5 connection kit

Case Size Range

Length: 6" - infinite
Width: 5.5" - 26"
Height: 3.5" - 24.5"
Optional 2.5" minimum box height available

Machine Dimensions

Width: 46.25" (128 cm)
Depth: 36.75" (94 cm)
Height: 67.5" (171 cm)

Specifications

Electrical: 110 VAC, 60 cycle, single phase
Air: N/A
Weight: 570 lbs (258 kg) uncrated

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.