



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David Legend Random Semi-Auto Case Sealer



At a Glance

- Industry standard semi-automatic random case sealer
- Light touch head paddle
- Patented leg extensions
- Interchangeable tape cartridges
- Patented safe single mast trolley system
- Reliable operation
- Heavy-duty steel construction
- Light touch roller switch

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Heavy-Duty Semi-Automatic Random Case Sealer

No adjusting needed for sealing random box sizes at speeds of 80 feet per minute.

The Little David Legend Random has a single mast, enclosed head lifting cylinder, head raising air switch and comes standard with extended side rails, and a roller in-feed table with integrated roller switch to operate rails.

Features

Plug in operation

Minimal operator training required

Sealed drive system

CaseLocker ST tape cartridge requires no lubrication

Front roller pack table

Patented single mast design allows clear access

Knife guard system of the CaseLocker ST tape cartridge exposes blade only when the rollers are depressed

Continuous belt drive

Operating Speed: Up to 80' per minute (24.4 m/min)

Seals with pressure sensitive tape

Converts from 2" to 3" wide tape

Options

- Casters
- Head limiter
- Pneumatic pass through
- Leg adjustments
- High mast for box heights to 34"
- Rear solid or roller pack table

Reliable Performance Warranty

- 1 year all components
 - 2 year warranty for gear reducer and motor
 - 3 year warranty for tape cartridge
- (Moving and wear parts are not included, other restrictions may apply)

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Legend Random Specifications

Case Range	Length: 6.5" (165 mm) - infinite Width: 4.5" (114 mm) - 20" (508 mm) Height: 4.5" (114 mm) - 24" (610 mm)
Operating Speed	Continuous belt drive 80' per minute (24.4 m/min)
Power	115 volts, 60 cycle, single phase
Machine Dimensions	Width: 56.75" (144.2 cm) Depth: 32" (81.2 cm) Height: 57.1875" (145.3 cm)
Machine Weight	275 lbs (125 kg) uncrated

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.