



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David SP-304 Semi-Auto Uniform Case Sealer



At a Glance

- Innovative T-rail infeed table for fast case processing
- Top 3 flap folder
- Bottom major flap folding bars
- Interchangeable tape cartridges
- Safe single mast system
- Reliable simple operation
- Heavy duty steel construction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Side Belt Taper with Extended Case Packing Rail

The Little David SP-304 Semi-Automatic has an innovative extended T rail packing table that increases productivity. This side belt tape sealer propels cartons through a folding section, then folds all major flaps and one upper flap. Repetitive motion is reduced and productivity is increased with this innovative design.

Features

- Plug in operation
- Minimal operator training required
- Sealed drive system
- CaseLocker ST tape cartridge requires no lubrication
- Alleviates twisting motion known to cause carpal tunnel syndrome
- Self-centering belts
- Continuous belt drive
- Operating Speed: Up to 72' per minute (18.3 m/min)
- Seals with pressure sensitive tape

Safe

- Patented single mast design allows clear access
- Knife guard system of the CaseLocker ST tape cartridge allows the blade to be exposed only when the

rollers are depressed

Options

Casters

Leg adjustments

Removable "T" rail pack table

Rear standard or roller pack table

Top hold down sled (for semi-automatic case former model)

High mast for box heights to 34"

Stainless steel

NEMA 4, NEMA 7

Reliable Performance Warranty

1 year all components

2 year warranty for gear reducer and motor

3 year warranty for tape cartridge

(Moving and wear parts are not included, other restrictions may apply)

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Case Size Range

Model	Tape Width	Description	Case Length	Case Width	Case Height
SP-304 I	2"	Side Belt Drive	6" - 24"	4.5" - 25"	4.5" - 24"
SP-304 II	2"	High Mast Side Belt Drive	6" - 24"	4.5" - 25"	4.5" - 34"
SP-304 III	2"	Bottom Only Side Belt Drive	6" - 24"	4.5" - 25"	4.5" - ∞"
SP-304 I	3"	Side Belt Drive	6" - 24"	5.5" - 20"	4.5" - 24"
SP-304 II	3"	High Mast Side Belt Drive	6" - 24"	5.5" - 20"	4.5" - 34"
SP-304 III	3"	Bottom Only Side Belt Drive	6" - 24"	5.5" - 20"	4.5" - ∞"

SP-304 Specifications

Operating Speed	Continuous belt drive 76' per minute (18.3 m/min)
Power	110 volts, 60 cycle, 80 Amps
Machine Dimensions	Width: 79.5" (202 cm) Depth: 33.5" (85 cm) Height: 59.25" (150 cm)
Machine Weight	300 lbs (136 kg) uncrated

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.