



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Pearson CS15 Case Sealer



At a Glance

- 15 to 29 cases per minute
- Fully-automatic
- Handles a wide-range of RSC and CSSC case sizes
- Seals with tape

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact Case Sealing up to 29 per Minute

Pearson CS15 Case Sealers handles a wide-range of RSC and CSSC case sizes. Featuring a compact size and continuous motion, the CS15 top seals at speeds of 15 to 29 cases per minute depending on case length. A convenient bypass option eliminates the need for additional conveying when pre-sealed boxes or HSCs are introduced into the line. Advanced features such as high-visibility machine status lighting, non-contact interlocks, CAT-3 Safety Circuits and an easily accessible grace port are standard on the machine.

Features

Case Squareness Protection: Spring loaded synchronous compensating side belts and squaring wheels ensure cases remain square throughout the closing and sealing process.

Fast Changeover: The machine design and accompanying changeover guide support intuitive and tool-less changeover to maximize machine uptime. Trained technicians can complete a changeover in under 2min.

Bypass Option for Pre-Sealed Boxes or Without Tops: No need to build by-pass conveyors when running cases not requiring sealing.

Safety Redundancy with CAT 3: Dual channel safety circuit maintains integrity of safety features in case of single component failure.

Easily Accessible Grace Port: Grace ports provide convenient communication access and 110V convenience outlet at the outside of the machine's electrical cabinet.

Remote Access Capability: Allows Pearson's support team on-demand access to the equipment's PLC and HMI through a secure VPN connection via an eWON router (ISECOM STAR and ISO27001 certified) to support emergency troubleshooting and reduce on-site visits.

Options

Additional tape head

Hand pack station

HMI

Oversized and undersized case support

Plant level ethernet connection

Portability

Tape sensing

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Speed	15 to 29 cases/min
Min. Case Size	6"L x 4.5"W x 3"H Extended case size range available
Max. Case Size	24"L x 16"W x 18.5"H Extended case size range available
Sealing	Tape
Operation	Pneumatic
Changeover	Manual, supported by scales, pointers, and quick release handles 2 min (estimate for trained technician)
Construction	Mild steel
Machine Size Range (ft)	5'L x 4'W x 5'H
Controls	Allen-Bradley PLC PackML Compliant
Air Requirements	80 PSI
Power Requirements	120 VAC
Disconnect Sizes	16 Amps
Air Consumption	0.016 SCF/Cycle
FLA (Full Load Amp) of Base Machine	6 Amps
Case Support	CSSC RSC

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.