



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Roach 700SBF Inclined Floor-to-Floor Slider Bed Belt Conveyor

At a Glance

- Floor-to-floor slider bed conveyor provides higher load capacity
- Reversible flow and nose-over allows for simple adjustments
- Simple adjustments for inclines 0-35

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Floor-to-Floor Conveyor Provides Higher Load Capacity

The Roach 700SBF floor-to-floor conveyor provides higher load capacity, reversible flow and nose-over allows for simple adjustments for inclines 0-35. Shown with optional supports, knee braces, chain driven feeder and right hand drive. All units furnished standard with left hand drive.

Specifications

Belting: Black PVC ruff-top.

Drive Pulley: 8" dia. with 1-7/16" dia. shaft, both machine crowned and fully lagged.

Tail Pulley: 4" dia., machine crowned, with 1-3/16" dia. shaft.

Return Rollers: 1.9" dia. x 16 ga. steel, model 196S, adjustable.

Center Drive: Reversible drive with 24" integral belt take-up.

Belt Speed: 60 FPM, constant.

Safety Pop-Out Roller: Standard on both ends, 1.9" dia. x 16 ga. steel roller, model 196S.

Nose-Over: Provides smooth transition from incline to horizontal position. Single nose-over adjusts 0-20°; double nose-over adjusts 0-35° (specify single or double).

Bearings: All pulley bearings are precision, heavy duty, lubricated, ball bearing units with cast iron housings.

Bed: 7" x 1-1/2" x 12 ga. channel frame with 14 ga. slider bed 9"-39" BF; 12 ga. slider bed 45" & 51" BF.

Roller Chain: Drive pulley is driven by No. 50 roller chain for 1-1/2 HP or less and No. 60 chain on larger drives. Chain take-up provided on motor base.

Motor Drive: 1/3 HP, 230/460/3, 60 cycle, ODP right angle gear motor.

Options

Belting: 3 ply, brown neoprene ruff-top. Consult factory for other belting.

Side Mounted End Drive: Available as option when necessary to move center drive for unit clearance. Minimum horizontal nose-over length required is 3' (2' horizontal may be used if product does not overhang conveyor OAW).

Bed: Available in boxed slider bed.

Undertrussed Bed: Available to provide clearance underneath unit at bed joint locations. Specify location for undertrussing and desired clearance underneath unit. Consult factory.

Floor Supports: Various height adjustable supports and knee braces available.

Powered Feeder: Integral belt feeder or separate chain driven belt feeder.

Motors: Available through 3 HP in TEFC, explosion proof, dirty duty, brake motor, 115/230/1, 575/3, etc.

Ceiling Hangers: 5/8" dia. threaded rod w/ hardware to attach rods (specify rod length) to conveyor.

Guard Rails: 1-3/4" x 1" formed channel (model GC), adjusts horizontally to 10" wider than belt and vertically to 6" above belt; formed steel fixed (model FSG) in 2", 4", 6", 8", 12", and 18" heights.

Belt Speed: Constant speed 3-120 FPM; DC variable speed; AC inverter variable speed. Other constant or variable speeds available.

Electrical Controls: Magnetic starter (one direction or reversible); One direction manual starter; Momentary start/stop push button station; Forward / reversing / stop push button station.

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.

Horsepower & Drives

HP @ 60 FPM	A MAX		B MAX	
	4" Drive	8" Drive	4" Drive	8" Drive
1/3	16-5/8"	17-5/8"	58-5/32"	58-5/32"
1/2	16-5/8"	17-5/8"	58-5/32"	58-5/32"
3/4	17"	17-5/8"	58-25/32"	58-25/32"
1	17-1/4"	17-5/8"	59-17/32"	59-17/32"
1-1/2	18-1/8"	18-1/8"	61-21/32"	61-21/32"
2	19"	19"	62-21/32"	62-21/32"

Roach 700SBF Conveyor Lengths & Unit Weights

Conveyor Length			10'	20'	30'	40'	50'	Deduct
BELT	BF	OAW	Unit Weights (lbs)					Per Foot
6"	9"	12"	392	506	621	735	849	11
12"	15"	18"	501	657	813	969	1125	16
18"	21"	24"	610	808	1006	1204	1402	20
24"	27"	30"	719	959	1199	1438	1678	24
30"	33"	36"	828	1110	1391	1673	1955	28
36"	39"	42"	937	1261	1584	1908	2231	32

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.