



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Roach CD280 2-Strand Chain Drag Conveyor with Diamond Tread Plate

At a Glance

- Diamond tread plate top plate between the chains
- Lexan window on drive train guard
- Great for conveying pallets or large rigid containers

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Chain Drag Conveyor with Diamond Tread Top Plate between Chains

The Roach CD280 2-Strand chain drag features an optional diamond tread top plate between the chains, a Lexan window on the drive train guard, as well as custom paint. Optional supports are available.

Chain drag conveyors are the most effective and efficient way to move heavy-duty loads and bulk materials. Chain drag conveyors are best suited for products with unusual conveying characteristics such as pallets or large rigid containers.

Specifications

Frame: 7 gauge formed boxed channel.

Carrier Chain: 82' No. 80 flat bar chain.

Wear Strip: UHMW long lasting wear strip, upper and lower.

Chain Centers: 24"

Chain Take-Up: Screw type located at tail end.

End Drive: Allows one-direction (unit) operation; add optional center drive for reversible application.

Chain Speed: 3.5 FPM constant.

Bearings: Heavy duty, lubricated, ball bearing unit with cast iron housings.

Capacity: Unit load not to exceed 3000 lbs.

Motor Drive: 3/4 HP, 230/460/3, – 60 cycle, Super "E" right angle gear motor.

Electrical Controls: Optional.

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.