



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Roach 196G 16 Gauge Galvanized Steel Gravity Roller Conveyors

At a Glance

- 1.9 inch diameter x 16 gauge galvanized steel rollers
- Straight and curved models
- Several widths

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Straight and Curved Model Numbers

Straight Section Model Number 196G-21-3-H-9:

196G-(between frames)-(roller centers)-(set high or low)-(length)

Curved Section Model Number 196GC-39-H-90:

196GC-(between frames)-(set high or low)-(degree)

Specifications

Rollers: 1.9" x 16 gauge galvanized steel tubing, model 196G, with smooth swaged ends.

Frames: Formed steel painted channel 3-1/2" x 1-1/2" x 10 ga. set high; 4-1/2" x 1-1/2" x 10 gauge set low.

Bearings: Integral plain ball bearings, zinc plated, grease packed.

Frame Capacity: 250 lbs. per roller, or 1300 lbs. maximum distributed live load per 10' section with supports at 10' centers; 3200 lbs. at 5' centers.

Couplings: Butt type.

Axles: 7/16" hex shaft, spring loaded.

Optional Frame: 4" @ 5.4 lbs. structural steel channel frame, rollers 3/16" high, may vary due to structural tolerances.

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.

Straight Section (Wt Lbs)

Nominal Roller Length	Between Frames	3" RC 10'	4.5" RC 10'	6" RC 10'	9" RC 10'	12" RC 10'
*6"	*7"	123	103	94	84	79
12"	13"	165	133	117	101	93
14"	15"	179	143	124	106	97
16"	17"	193	152	132	112	102
18"	19"	207	162	140	118	107
20"	21"	221	172	148	123	111
22"	23"	234	182	155	129	116
24"	25"	248	191	163	135	120
26"	27"	262	201	171	140	125
30"	31"	290	221	186	152	134
32"	33"	304	231	194	157	129
36"	37"	332	250	209	168	148
38"	39"	346	260	217	174	153
42"	43"	374	280	233	185	162
46"	47"	401	299	248	197	171
50"	51"	429	319	263	208	180

*7" BF straight sections furnished with spring loaded shafts in set high position only.

Curved Section (Wt Lbs)

Nominal Roller Length	Between Frames	Curve Inside Radius	Curve Roller Design	90° Rollers per Curve	90° Wt. lbs.	45° Rollers per Curve	45° Wt. lbs.
*6"	*7"	-	-	-	-	-	-
12"	13"	2'-8-1/2"	Single	22	217	11	120
14"	15"	2'-8-1/2"	Single	22	246	11	134
16"	17"	2'-8-1/2"	Single	22	274	11	147
18"	19"	2'-8-1/2"	Single	22	303	11	161
20"	21"	2'-8-1/2"	Single	22	331	11	175
22"	23"	2'-8-1/2"	Double	41	360	21	188
24"	25"	2'-8-1/2"	Double	41	388	21	202
26"	27"	2'-8-1/2"	Double	41	417	21	216
30"	31"	4'	Double	40	474	20	243
32"	33"	4'	Double	40	503	20	257
36"	37"	4'	Double	40	560	20	284
38"	39"	4'	Double	40	589	20	298
42"	43"	4'	Double	40	646	20	325
46"	47"	4'	Double	40	703	20	353
50"	51"	4'	Double	40	760	20	380

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.