

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com

Roach 3530S Structural .300 Steel Gravity Roller Conveyor

At a Glance

- 3-1/2 inch diameter x .300 steel rollers
- 2500 lbs. per roller
- Several widths

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Straight Model Numbers

Straight Section Model Number 3530S-47-6-H-7:

3530S-(between frames)-(roller centers)-(set high or low)-(length)

Specifications

Rollers: 3-1/2" x .300 steel tubing, model 3530S, with straight ends, reamed to provide smooth bearing

seats.

Roller Capacity: 2500 lbs. per roller. Bearings: Precision ABEC bearings.

Frames: 5" at 6.7 lbs. structural steel painted channel.

Frame Capacity: 6600 lbs. maximum distributed live load per 10' section with supports at 10' centers;

16,000 lbs. at 5' centers. **Couplings:** Butt type.

Axles: 1-1/16" hex shaft with pinned shafts.

Please contact Pro Pac or call 888-318-0083 for your conveyors.

Straight Section (Wt Lbs)

Nominal Roller Length	Between Frames	4" RC 10'	6" RC 10'	8" RC 10'	12" RC 10'
6"	7"	364	288	250	212
10"	11"	500	379	318	257
14"	15"	635	469	386	303
18"	19"	771	560	454	348
22"	23"	907	650	522	393
26"	27"	1043	741	589	438
30"	31"	1178	831	657	484
34"	35"	1314	1235	980	726
38"	39"	1450	1012	793	574
42"	43"	1586	1103	861	619
44"	45"	1653	1148	895	642
46"	47"	1721	1193	929	665
50"	51"	1857	1284	997	710

Please contact Pro Pac or call 888-318-0083 for your conveyors.