



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Roach CVC Vertical Conveyor



At a Glance

- Vertically conveys up to 3000 lbs
- No operator, automatic loading by metered belt
- Up to 25 loads per second
- Four continuous roller chains driven by a brake motor

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Specifications

Capacity: Up to 3000 lbs.

Frame: Heavy-duty tubular construction.

Drive: Four (4) continuous roller chains driven by a suitably sized brake motor.

Rate: Up to 25 loads per minute.

Speed: 60 FPM (100 FPM maximum).

Loading: Automatic loading is accomplished by metering belt. Operator attention is not required.

Platform: Size depends upon product.

Guards: Expanded metal guarding.

Electrical Controls: Supplied as required.

Please [contact Pro Pac](mailto:solutions@propac.com) or call 888-318-0083 for your conveyors.

Platform Dimensions & Capacity

CV Number	Carrier Platform Dimensions		Platform Capacity
	Length	Width	
60	3" increments up to 49-1/2"	18"-60"	200
80	4" increments up to 78"	24"-84"	600
100	5" increments up to 90-1/2"	30"-96"	1000
122	6" increments up to 105"	36"-96"	2000
143	8" increments up to 108"	36"-96"	3000

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.