



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Roach IPT Heavy-Duty Indexing Powered Turntable

At a Glance

- Turn products around in tight quarters
- Convey heavy unit loads
- Orient product at specified intervals for operators to perform tasks

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Index Product Around at Intervals in a Small Space

Roach IPT heavy-duty indexing powered turntables convey heavy unit loads in numerous applications. A heavy-duty chain driven live roller may be mounted on turntable platform and rotated to orient product at specified intervals allowing operator to perform a variety of tasks.

Specifications

Rotation: 2 position, 3 position or 4 position.

Speed: 35 FPM at outside diameter.

Chain Drive: No. 80 roller chain.

Chain Guard: The chain drive is completely enclosed.

Casters: Eight (8) 4" dia. heavy duty rubber-covered casters support rotation of turntable carrier platform.

Diameter: 3'-0", 3'-6", 4'-0", 4'-6", 5'-0", 5'-6", 6'-0", 6'-6", 7'-0", 7'-6" and 8'-0" dia.

Carrier Platform: 3" structural platform with 1/2" thick steel plate supported by heavy duty casters.

Bearings: Heavy duty ball bearing 4-hole flange.

Capacity: 4000 lbs. max. product load.

Motor Drive: 3/4 HP, 230/460/3, 60 cycle, TEFC right angle gear motor with brake.

Elevation: Minimum 12-1/2" to top of plate with four (4) structural leveling supports.

Electrical Controls: Limit switches supplied as follows: 2 position = 2 limit switches; 3 position = 3 limit switches; 4 position = 4 limit switches.

Options

Elevation: Other height elevations to top of plate available; consult factory.

Motors: Available through 2 HP in TEFC, explosion proof, dirty duty, 115/230/1, 575/3, etc.

Electrical Controls: Manual start/stop push button switch; magnetic starter; limit switch; photo relay; others available.

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.

Widths & Weights

A	B	Weight (lbs)
3'	53-3/4"	718
3'-6"	59-3/4"	814
4'	65-3/4"	926
4'-6"	71-3/4"	1037
5'	77-3/4"	1158
5'-6"	83-3/4"	1285
6'	89-3/4"	1421
6'-6"	95-3/4"	1564
7'	101-3/4"	1718
7'-6"	107-3/4"	1877
8'	113-3/4"	2045

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.