



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Roach 700FFT 900 Series Flat Friction Top Plastic Belt Conveyor

At a Glance

- For floor-to-floor, inclined or declined carton handling applications
- Eliminate belt tracking problems with plastic belt
- Constant 60 FPM

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Consistently Move Cartons Across Your Floor Level, Incline or Decline

The Roach 700FFT 900 Series Flat Friction Top Plastic Belt Conveyor is a perfect choice for floor-to-floor, inclined or declined carton handling applications. Eliminate belt tracking problems with plastic belt on this 700FFT conveyor.

Specifications

Belting: Series 900 flat friction top gray polypropylene belt with black rubber top modules.

Drive Sprockets: 6.1" pitch dia. with 1.5" square bore. Available with optional 6.1" pitch dia. with 2.5" square bore and 6.8" pitch dia. sprockets with 1.5" or 2.5" square bore.

Tail Sprockets: 6.1" pitch dia. with 1.5" square bore. Available with optional 6.1" pitch dia. with 2.5" square bore and 6.8" pitch dia. sprockets with 1.5" or 2.5" square bore.

End Drive: Allows one-direction (unit) operation.

Belt Speed: 60 FPM, constant.

Take-Up: Catenary type located at discharge end.

Return Rollers: 1.9" dia. x 16 ga. steel, model 196S, adjustable with rubber sleeves.

Bed: 7" x 1-1/2" x 10 ga. channel frame with open style bed construction and UHMW wearstrips mounted to longitudinal channels.

Bearings: Drive and tail shaft bearings are precision, heavy duty, lubricated, ball bearing units with cast iron housings.

Roller Chain: Drive shaft is driven by No. 50 roller chain for 1-1/2 HP or less and No. 60 chain on larger drives. Chain take-up provided on motor base.

Motor Drive: 1/3 HP, 230/460/3, 60 cycle, ODP right angle gear motor.

Floor Supports: Many options available.

Electrical Controls: Optional.

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.

PPF Available Belt Widths

Width	BF	OAW
6"	7"	10"
12"	13"	16"
18"	19"	22"
24"	25"	28"
30"	31"	34"
36"	37"	40"
42"	43"	46"
48"	49"	52"

Please [contact Pro Pac](#) or call 888-318-0083 for your conveyors.