



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# SpanTech EZ Span Belt Conveyor

## At a Glance

- Modular chain instead of a fabric belt
- Sprocket driven unit designed for easy maintenance and no tracking issues
- Take-up units are not placed at the ends of the conveyor to ensure a consistent length

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



## Consistent Conveyor Spanning

The SpanTech EZ Span uses extremely-thin, modular conveyor chain to create a system that has many advantages over typical belt conveyor designs including: capability, maintenance, and price.

With a modular chain instead of a fabric belt, the EZ Span belt conveyors eliminate any tracking issues that are considered normal with belt conveyors.

Take-up units are not placed at the ends of the conveyor. Your conveyor length will never deviate. EZ Span conveyors fit in perfectly between machines without the take-up unit creating a huge gap or interfering with the machinery.

## EZ Span Benefits

Low cost.

Quick delivery.

Plastic modular chain instead of a fabric belt.

Sprocket driven unit designed for easy maintenance and no tracking issues.

Constant end-to-end distance with no take-ups on the end.

Very low-profile for easier integration.

Designed for simple maintenance.

Left or right drive capabilities.

Variable frequency drive included.

Automatic chain take-up with tension sensor.

## EZ Span Specifications

Chain width: 300mm (11.8").

Conveyor length: 730mm (2.4 ft) to 9145mm (30 ft).

Speed range: 30 ft/min to 110 ft/min.

Max load capacity: 250 lbs.

VFD included with your choice: 120/240 VAC (1P) | 240 VAC (3P) | 480 VAC (3P).

Roller ends: 38mm Ø of chain.

## Options

2 Chain styles: 6mm plain and 6mm raised.

Low profile nose bar option: 18mm (0.71") diameter.

Supports.

Casters.

Guide rail.