



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Hayssen RT2000 Horizontal Flow Wrapper



## At a Glance

- High-speeds with hermetic seals
- Perfect for modified atmosphere packaging
- Dual lane model available for smaller packages and higher speeds
- Optional C-fold package style with multiple reclose options

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

BW Flexible Systems's RT series of HFFS systems feature a unique long dwell sealing system that creates hermetic seals at high-speeds.

Available in single and dual lane, the RT2000 is perfect for modified atmosphere requirement and features MAGNUM dies for improved end seals, film edge tracking, closed loop heat control with high and low heat temperature alarms for individual dies, constant film tension, and unwind brake system with roll diameter feedback.

The RT2000's tubular front and rear frame allow for easy access and built to withstand severe operating environments and stringent sanitation procedures. The Allen-Bradley ControlLogix platform with PV+1000 Versaview color touch screen is user-friendly and simplifies programming.

## Features of the RT2000

Unique die wheel design creates an extended sealing dwell time to produce the best seals at high speeds

Perfect for modified atmosphere packaging (MAP) requirements

Change package size without any parts change

Allen-Bradley ControlLogix platform with AB Panelview Plus 1000 color touchscreen

Tubular frame is built to withstand severe operating environments and stringent sanitation procedures

Dual lane model available for smaller packages and higher speeds

Optional C-fold package style with multiple reclose options

Cantilevered pneumatic film spindle

Separate motor drive on discharge conveyor tabletop chain

## Options

Stainless steel construction  
Gas flushing for one or two gases  
C-fold package  
Zipper-ready features  
Hole punches  
Product guides on exit conveyors  
Servo infeed drives  
Product jam detection  
Misplaced product detection

## Package Range

Product Width: 1.75" to 13" (45mm to 330mm)  
Product Length: 4.25" to 14" (108mm to 355mm)  
Product Height: 0.5" to 3" (13mm to 76mm)

## Production Rate

Up to 200 ppm or linear film speed of 2000 inches per minute  
High-speed option allows for 250 ppm  
Dual-lane option allows for 500 ppm

## Power and Air Requirements

Power Supply: 230V, 50/60 Hz, 30 amp  
Air Supply: 3 scfm at 65 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your fin seal flow wrapping equipment.