



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Hayssen RT2000 Horizontal Flow Wrapper



At a Glance

- High-speeds with hermetic seals
- Perfect for modified atmosphere packaging
- Dual lane model available for smaller packages and higher speeds
- Optional C-fold package style with multiple reclose options

Buy your [flow wrapping film](#) from us, and get a discount on this BW Flexible Systems flow wrapper!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

BW Flexible Systems's RT series of HFFS systems feature a unique long dwell sealing system that creates hermetic seals at high-speeds.

Available in single and dual lane, the RT2000 is perfect for modified atmosphere requirement and features MAGNUM dies for improved end seals, film edge tracking, closed loop heat control with high and low heat temperature alarms for individual dies, constant film tension, and unwind brake system with roll diameter feedback.

The RT2000's tubular front and rear frame allow for easy access and built to withstand severe operating environments and stringent sanitation procedures. The Allen-Bradley ControlLogix platform with PV+1000 Versaview color touch screen is user-friendly and simplifies programming.

Features of the RT2000

Unique die wheel design creates an extended sealing dwell time to produce the best seals at high speeds

Perfect for modified atmosphere packaging (MAP) requirements

Change package size without any parts change

Allen-Bradley ControlLogix platform with AB Panelview Plus 1000 color touchscreen

Tubular frame is built to withstand severe operating environments and stringent sanitation procedures

Dual lane model available for smaller packages and higher speeds

Optional C-fold package style with multiple reclose options

Cantilevered pneumatic film spindle

Separate motor drive on discharge conveyor tabletop chain

Options

Stainless steel construction

Gas flushing for one or two gases
C-fold package
Zipper-ready features
Hole punches
Product guides on exit conveyors
Servo infeed drives
Product jam detection
Misplaced product detection

Package Range

Product Width: 1.75" to 13" (45mm to 330mm)
Product Length: 4.25" to 14" (108mm to 355mm)
Product Height: 0.5" to 3" (13mm to 76mm)

Production Rate

Up to 200 ppm or linear film speed of 2000 inches per minute
High-speed option allows for 250 ppm
Dual-lane option allows for 500 ppm

Power and Air Requirements

Power Supply: 230V, 50/60 Hz, 30 amp
Air Supply: 3 scfm at 65 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your fin seal flow wrapping equipment.