



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Schib CO 50 Horizontal Flow Wrapper



CO 50

## At a Glance

- Four models, customized for your packaging requirements
- Hygienic and easy-to-clean design
- No product - no bag feature minimizes film waste
- Icon-based operator interface with real time diagnostics

Buy your [flow wrapping film](#) from us, and get a discount on this BW Flexible Systems flow wrapper!

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

The BW Flexible Systems Schib CO 50 is a new generation horizontal flow wrapper suitable for a wide range of primary or secondary packaging applications. This versatile HFFS system offers compact construction, ergonomic and easy-to-clean design, as well as great flexibility and reliability.

The machine comes with top or bottom unwind, speeds up to 200 ppm, 3-axis drive configuration and the choice of Rotary, D-Cam or long-dwell jaws. Allen-Bradley controls are an available option.

Further options include twin jaws configuration, automatic film splicer, motorized film pre-feed, reel run out sensor, pre-printed film registration, no product – no bag function to minimize film waste, gusset tucking, Euro-slot, remote service device, and many other accessories. Automatic feeders and product conveying/handling devices are also available on demand.

## Features of the Schib CO 50

Hygienic and easy-to-clean design suitable for a wide range of industries (both food and non-food products)

Flexible and reliable

Fast format changeover with minimal downtime

7" color touch screen offering user-friendly HMI functionality

Icon-based operator interface with real time diagnostics

500 mm film width, 700 mm optional

All product contact parts are made of stainless steel or food grade plastic

All stainless steel version on demand

Independent temperature control circuits incorporated into the control panel

Product-specific infeed and automatic feeders are available on demand

## Schib CO 50 Models

CO 50: Top reel, rotary sealing head

CO 50TG: Top reel, box motion sealing head

CO 50BB: Bottom reel (inverted), rotary sealing head

CO 50BBTG: Bottom reel (inverted), box motion sealing head

## User-Friendly Controls

Control system with industry standard Allen Bradley PLC

Operator interface with 10" TFT color touch screen

50-program memory, expandable

3-axis drive technology

No-product / no-bag system

Service mode for diagnostics, trouble shooting and basic machine configuration, different level (user configurable) password-protection

Additional user-defined password level for limiting/ excluding access to selected machine functions, setting changes and sensitive data

## Package Range

Product Length: 1.96" to 18.89" (50mm to 480mm)

Product Width: 0.19" to 7.87" (5mm to 200mm)

Product Height: Up to 4.72" (120mm)

## Packaging Speed

Up to 200ppm, depending on film and product

## Power and Air Requirements

Power Supply: 480V, Three Phase, 60 Hz

Air Supply: 6 bar

Please [contact Pro Pac](#) or call 888-318-0083 for your fin seal flow wrapping equipment.