



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Schib CO 90E Candy Wrapper

At a Glance

- High-speed wrapper for hard candy and chewing gum
- Up to 2,000 ppm
- Disk feeder
- Twin reel holders with automatic splicer as an option

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



CO 90E

The industry-leading BW Flexible Systems Schib CO 90E horizontal flow wrap machine is specifically designed for candies and other small size confectionery products such as pellets, bubble gums, lozenges, toffees, tablets, and lollipops.

Its design evolves from 50 years of industry expertise and engineering excellence, coupled with the ultimate automation and motion solution from Allen-Bradley.

Several configurations of this model are available, including lollipop versions, customized feeders for hard-boiled candies, molded products and marshmallows, and multi-feeders for balls to be wrapped in assorted colors.

Features of the Schib CO 90E

High speed wrapper for hard candy and chewing gum

Up to 2,000 ppm

User-friendly controls

Allen-Bradley programmable automation controller

10" color touch HMI screen

Allen-Bradley Kinetix servo drives

Disk feeder

Twin reel holders with automatic splicer as an option

Reel run out sensor

Motorized film pre-feed

Photocell registration for printed film

Serrated end seals for easy opening

Temperature control integrated into control panel
2 to 6 jaws configurations

Schib CO 90 E

Designed to wrap small hard candy
Has its own bowl feeder and feeding disc custom-sized for the product
1500 to 2000 ppm

Schib CO 90 L

Designed to overwraps entire lollipops, candy and stick
Up to 550 ppm

Schib CO 90

Designed to wrap narrow product under 80mm / 3" wide, such as nutrition bars
Typically integrated with an automatic row removal system upstream that supplies product at a consistently high rate
Up to 500 ppm

User-Friendly Controls

Control system with industry standard Allen Bradley PLC
Operator interface with 10" TFT color touch screen
50-program memory, expandable
3-axis drive technology
No-product / no-bag system
Service mode for diagnostics, trouble shooting and basic machine configuration
Password protected levels for limiting / excluding access to selected machine functions, setting changes and sensitive data

CO 90E Package Range

Product Length: 0.59" to 1.96" (15mm to 50mm)
Product Width: 0.19" to 1.18" (5mm to 30mm)
Product Height: Up to 1.18" (30mm)

CO 90L Package Range

Product Length: 3.14" to 4.72" (80mm to 120mm)
Product Width: 0.19" to 1.96" (5mm to 50mm)
Product Height: Up to 1.96" (50mm)

CO 90 Package Range

Product Length: 1.96" to 7.87" (50mm to 200mm)
Product Width: 0.19" to 3.15" (5mm to 80mm)
Product Height: Up to 2.36" (60mm)

Power and Air Requirements

Power Supply: 480V, Three Phase, 60 Hz
Air Supply: 6 bar

Please [contact Pro Pac](#) or call 888-318-0083 for your fin seal flow wrapping equipment.