



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

PFM BG 4800 Horizontal Flow Wrapper

At a Glance

- Up to 160 products per minute
- Creates reclosable MAP packages
- Easy cleaning with AISA 304 steel for all product contact points
- Color touch screen HMI

Buy your [flow wrapping film](#) from Pro Pac, and get a discount on this PFM flow wrapper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



High Speed Reclosable MAP Packages

The PFM BG 4800 produces flow wrapped packages with three seals that have a perfect appearance. Designed for high-speed packaging with Modified Atmosphere Packaging. The BG 4800 creates completely air tight seals, that are compact, smooth, and free from wrinkles.

Recloseable bag system allows your products package to be resealed with a resealable tab or with an adhesive strip or zipper. Ideal for all types of food products that would be consumed in more than one stage, the resealable packaging helps preserve product freshness.

The easy-open and recloseable system offers marketing advantages for your products to your consumers.

Benefits

Cleaning: In just a few minutes, the BG 4800 can be completely cleaned. All parts are within reach, easily accessible, and extractable. All parts that come in to contact with your products are made of AISI 304 steel.

Multi-Jaw Crossways Prolonged Sealing Unit: High pressure and a prolonged sealing time are the distinguishing factors of the exclusive BG Pack rotating multi-jaw system. The material remains tight, stretched between the jaws thus making it impossible for wrinkles and defects to form. Each jaw has separate temperature controls monitored via the machine touch screen. If the temperature of any the jaws fluctuates out of the selected range the machine stops automatically with the defective jaw in a quick removal position.

User Friendly: Color screen touch panel provides simplicity in each programming stage.

Quick Fitting and Removal Jaw System: In just a few minutes, the versatile jaws can be released or repositioned. Essential for MAP packaging, the crimping jaws provide completely air-tight seals.

Control and High Performance: The rotating multijaw crossways sealing system with a prolonged sealing time produces up to 160 packages a minute. The longitudinal linear shoe sealing provides smooth and resistant seals. State-of-the-art electronics accurately controls the wrapping of printed material.

Features

Up to 160 packs per minute with pillow bag

Multi-jaw sealing method, Min 7, Max 22

Expansion reel holding unit shaft with electronically controlled brake

Production and sell-by date printing device (optional)

Electrical function relying on independent motors and industrial PC

Manufactured in AISI 304

Discharge conveyor with 180° bevel rollers with work surface level discharge

Open & Reclose Package Features

Allows modified atmosphere packaging (MAP) with the utmost safety

Package opens easily, without the need to use cutting utensils

Film barrier characteristics and the resealability allow product to be consumed in more than one stage

Resealable tab allows protection of the product, extending its preservation from the moment it is opened

Greater printable area for consumer information and market promotion

Pillow Bag Dimensions

Product width: 1.77" - 7.08" (45mm - 180mm)

Product height: 0.39" - 3.15" (10mm - 80mm)

Product length: 2.76" - 12.6" (70mm - 320mm)

Cut Off bag: 4.13" - 13.97" (105mm - 355mm)

Max flat bag: 7.08" (180mm)

Web film: 17.32" (440mm)

Easy Pack Dimensions

Product width: 2.36" - 7.08" (60mm - 180mm)

Product height: 0.39" - 1.77" (10mm - 45mm)

Product length: 2.76" - 10.63" (70mm - 270mm)

Cut off bag: 4.13" - 11.81" (105mm - 300mm)

Max flat bag: 7.08" (180mm)

Web film: 17.32" (440mm)

3 Side Seal Bag with Zipper Dimensions

Product width: 2.36" - 5.9" (60mm - 150mm)

Product height: 0.39" - 1.77" (10mm - 45mm)

Product length: 2.76" - 10.63" (70mm - 270mm)

Cut off bag: 4.13" - 11.81" (105mm - 300mm)

Max flat bag: 7.08" (180mm)

Web film: 14.17" (360mm)

Specifications

Electrical: 400V, 3 Phase, 50/60 Hz, 10Kw consumption

Machine length: 184.64"L x 55.12"D x 86.61"H (4690mm x 1400mm x 2200mm)

Machine weight: 3,307 lbs (1500 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your fin seal flow wrapping equipment.