



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

PFM Zephyr Horizontal Flow Wrapper

At a Glance

- Designed to run on multi-shift operations
- 4 servo driven axis
- Designed for easy cleaning

Buy your [flow wrapping film](#) from Pro Pac, and get a discount on this PFM flow wrapper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Rugged All-Day Flow Wrapper

The electronic PFM Zephyr is designed to run on multi-shift operations. Built with a cantilevered main frame, the Zephyr completely separates product packaging and drive elements. Complete this flow packing machine with a series of loaders for automatic feeding.

The PFM Zephyr servo-assisted horizontal flow wrapper produces packages hermetically sealed on three sides. The machine has been designed with cantilevered main frame and matched perfectly to a series of automatic feeding systems. Ideal for medium speed packaging.

Cantilevered machine construction houses mechanical and electrical components at the back of the machine. The front is free from obstruction, and quick and easy to clean in every point.

Features

- Fully-cantilevered frame with separation plate
- 4 servo driven axis
- 4 finwheel units (i.e. cold, two heated, fold-over)
- Heat and cold sealing equipment
- Servo driven unwind feed rollers
- Automatic film splicer
- Pneumatic blocking double reel holders
- Color touch screen
- Display on machine status, diagnostic, production data, and alarms
- Product contact parts made of stainless steel
- Chain with cantilevered pusher fitting
- Two-way print registration unit

Driven top brush at discharge belt
Ejector for empty or double packages
Complete series of infeed conveyors

Options

Coding and reading device
Cooling plate on longitudinal sealing wheels
Plate-top chain
Vacuum system
Modified atmosphere packaging
No gap / no seal function
No product / no paper function
Long-dwell crimper unit
Mechanical or air gussting device
Full stainless steel version

Product Dimensions

Length: 0.39" - 13.78" (10mm - 350mm)
Width: 0.39" - 12.6" (10mm - 320mm)
Height: Up to 3.15" (80mm)

Specifications

Cut off length: 1.97" - 13.78" (50mm - 350mm)
Film width: 15.75" (400mm)
Film roll max OD: 13.78" (350mm)
Core diameter: (70 - 76mm)
Electrical consumption: 9kw
Machine weight: 2,425 - 2,866 lbs (1,100 - 1,300 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your fin seal flow wrapping equipment.