



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Redpack HC65 High Care Horizontal Flow Wrapper

At a Glance

- Wash down design
- IP65 rated infeed and discharge
- Quick change over

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Wash Down Design for Fast Cleaning

The Redpack HC65 is an IP65 (ingress protection) rated bottom-seal flow wrapping machine. Designed to minimize debris traps with no flat horizontal surfaces and sealed structural sections, the HC65 is easy to maintain and keep clean.

Redpack HC65 discharge and infeed are manufactured to an IP65 (water proof 30mins<1m) rated specification. The discharge is designed for quick removal from the flow wrapper. The infeed has a cantilevered construction with drop down side and a quick-release chain for easy and fast cleaning - ideal for busy pack houses where downtime must be kept to a minimum.

Constructed entirely from stainless steel (304/303) & Acetal Co-polymer which offer excellent resistance to corrosion and most sanitizing chemicals. Resistance to specific sanitizing chemical and stainless steel 316 (approved for food contact) can also be offered in addition to full material certification.

Simple Interface and Quick Change Over

With a multi-axis drive, the HC65 is designed for product flexibility. The touch screen HMI offers a simple operator interface for easy parameter entry and quick product changeover.

Features

Horizontal surfaces minimized with 3° runoff.

Ergonomic design allowing for user friendly operation.
4 sets of configurable seam crimps.
Auto stoppage function to prevent seal degradation.
Configurable infeed to suit application.
Rotary end-crimp configurable to suit application.
Quick access to infeed internals to facilitate hygienic operation.
Adjustable fold box.
Compliant to relevant CE standards.
No product, no bag.
No gap, no crimp.
Integrated safety PC facilitating safety zones.
Upstream/downstream connections for line integration.
Simple removal of seam crimp module for off line maintenance.

Please [contact Pro Pac](#) or call 888-318-0083 for your horizontal flow wrapping equipment.