



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Redpack NTS-BM Box Motion Top-Seal Horizontal Flow Wrapper

At a Glance

- Box motion end end seal
- Hermetic and water-tight seals
- Touch screen HMI with recipe storage

Buy your [flow wrapping film](#) from Pro Pac, and get a discount on this Redpack flow wrapper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Hermetic Water Tight Seals - Ideal for the Medical Industry

The Redpack NTS-BM box motion top seal flow wrapper, robustly built with stainless steel, is designed to wrap products that require high-integrity hermetic seals with a long-dwell sealing process.

State-of-the-Art Technology

The Redpack NTS-BM box motion top-seal flow wrapping machine has an advanced multi-axis electronic drive system that has a 10.3" color touch screen (HMI). Using simple commands the operators can quickly adjust the machine to suit different products. Bag length, print registration, end crimp slow down, infeed position, printed code position and machine speed are all changed automatically by entering a product name on the touch screen.

Simple Fast Product Change Over

Using simple commands, operators quickly adjust the machine to package different products. Recipe storage allows bag length, print registration, end crimp slow down, infeed position, printed code position and machine speed to be changed automatically by simply entering a product name on the touch screen.

Features

The machine is equipped with independent drives synchronized through the servo-control system.

Machine is fabricated from solid stainless steel base.v

Lifting frame integral chassis of flow wrapper.

Independent temperature control of the welding jaw heaters.

Integrated holder for a thermal transfer printer.

Option for integrated label applicator.

Pneumatic film mandrel with a scale for easier and more efficient operation of the machine.

Electronically driven film axis for the most efficient machine operation with the auto film tension.

Electrically adjustable height of the longitudinal welding module.

No product, no bag.

Modem for remote control and machine diagnostics for the fastest response.

Please [contact Pro Pac](#) or call 888-318-0083 for your horizontal flow wrapping equipment.