



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Syntegon Pack 201 Horizontal Flow Wrapper



## At a Glance

- A large variety of mid-range, multi-purpose applications
- Servo controls and pre-programmable recipes
- Mechanical adjustments are easy and repeatable
- Up to 450 packages per minute

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Large Variety of Mid-Range, Multi-Purpose Applications

A large variety of mid-range, multi-purpose applications are covered by the Syntegon Pack 201 wrapper. Servo controls and pre-programmable recipes are ideal for applications where flexibility and fast changeovers are required. Mechanical adjustments are easy to make and are repeatable. The infeed, finwheels and cutting head are cantilevered for sanitation for easy cleaning and reduced maintenance.

The Pack 201 wrapper is easy to maintain. Its proven reliable technology uses the highest quality parts to minimize downtime. The electrical panel is enclosed and completely separated from the mechanics of the machine.

## Pack 201 HS

A high-speed version of the standard Pack 201, the Pack 201 HS increases the maximum film speed 50% up to 60 m/min producing up to 450 packages/min in a 3-up configuration.

## Benefits

Flexible design can handle a wide range of applications

Fast changeovers for packaging various sized products

High sanitation level for easy cleaning

Proven, reliable Syntegon technology uses high quality parts, minimizing downtime and increasing machine lifetime

## Applications

A large variety of mid-range, multi-purpose applications are covered by the Pack 201 wrapper. The wrapper is perfect for products such as soft bakery items, trays, candy, biscuit stacks and other food and non-food items that require mid-range speed.

## Options

- Rockwell Automation (AB) ControlLogix with touchscreen
- Second film reel holder with manual splice table
- Brackets for printer
- Low film detection
- Automatic film splicer
- Preheating between the first and second finwheel pair
- Air evacuation for tight packages
- Gusseting device
- Hole punch device
- No product - no bag feature (reduces film waste)
- No gap - no seal (reduces jams)
- Air reject of incorrect or empty packages
- Gas flushing
- Stainless steel execution

Please [contact Pro Pac](#) or call 888-318-0083 for your flow wrapping equipment.

## Specifications

Product Dimensions	Length: 40 mm (1.5") - 565 mm (22.2") Width: 12 mm (0.5") - 250 mm (9.8") Height: 6 mm (0.23") - 110 mm (4.3")
Standard Capacity	1-Up: Up to 150 bags/min 2-Up: Up to 250 bags/min Film Speed: Up to 40 m/min
High Speed Capacity	1-Up: Up to 300 bags/min 2-Up: Up to 450 bags/min Film Speed: Up to 60 m/min
Web Dimensions	Reel Diameter: Max. 400 mm (15.7") Width: Max. 650 mm Weight: Max. 35 kg

Please [contact Pro Pac](#) or call 888-318-0083 for your flow wrapping equipment.