



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Syntegon Pack 401 Horizontal Flow Wrapper

## At a Glance

- Proven features that provide a high degree of reliability and efficiency
- Gap control results in consistent and precise seal integrity
- Standard dual spindle backstand
- Up to 800 packages per minute

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



## Reliable, Efficient, Precise Flow Wrapping

The Syntegon Pack 401 horizontal flow wrapper combines proven features that provide a high degree of reliability and efficiency. The latest technology in gap control results in consistent and precise seal integrity. A standard dual spindle backstand with power feed roller allows for full automation, providing improved splicing, cutting, auto tracking and tight cut offs.

The Pack 401 flow wrapper can operate as an independent unit or can be integrated with other packaging systems such as Delta-robotics, secondary packaging equipment, product handling equipment, and various infeed modules.

## Benefits

Fast, reliable automation for high production volumes

Low TCO (total cost of ownership), thanks to durable construction, long life time, low maintenance levels and high operating efficiency

High-quality package appearance ensured through state-of-the-art film handling and sealing technology

## Applications

The Pack 401 flow wrapper covers a large variety of high-end applications and is ideal for handling bakery and confectionery items such as biscuits, chocolate and bar-type products, as well as non-food products and much more.

## Flowpack Styles

Pillow  
Gusseted  
Zig zag knife  
Hole punch  
Opening aids

## Options

Self-centering film roller  
End of roll / film breakage detection  
Auto splice with knife mechanism  
Automatic film tracking  
Separate drive on first finwheel set  
Cold seal unwind peeling rollers  
Air evacuation manifold  
Gusseting device  
No product - no film feature  
No gap - no seal feature  
Air reject of incorrect or empty packages  
Adjustable folding box  
Rockwell Automation (AB) ControlLogix machine control

Please [contact Pro Pac](#) or call 888-318-0083 for your flow wrapping equipment.

## Specifications

Product Dimensions	Length: 40 mm (1.5") - 565 mm (22.2") Width: 12 mm (0.5") - 250 mm (9.8") Height: 6 mm (0.23") - 110 mm (4.3")
Capacity	Output: Up to 800 bags/min Film Speed: Up to 80 m/min
Web Dimensions	Reel Diameter: Max. 400 mm (15.7") Inner Core Diameter: 70/76 mm (2.8/3") Weight: Max. 40 kg

Please [contact Pro Pac](#) or call 888-318-0083 for your flow wrapping equipment.