



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation 250v3 Friction Feeder



At a Glance

- Maximum product width: 200mm (7.87in)
- Low-cost low-demand feeder
- Small footprint better integrates into your production line
- Same quality and performance of the larger machines

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact Low-Cost Feeder

The MFT Automation v3 Signature Series are economical, cost-effective friction feeders. Designed and built with the same quality as the premium ip feeders, the v3 Signature Series is engineered for lower throughput applications. With a powerful 500-watt two-thirds horsepower brushless servo motor, computer controls, and four different discharge lengths available makes the Signature Series friction feeder a top contender in its class.

The Signature Series feeders are a strong, robust and reliable lower-demand machines for simpler applications providing dependability on the production floor.

The MFT Automation 250v3 friction feeder has the same compact and versatile qualities, and feeds all the same products, as the 250ip3 friction feeder. Like the 250ip3 with its advantage in a compact size, the 250v3 feeder will also better integrate into your production line and time and cost savings will be apparent.

When small products are needed to feed and high speed is not essential, combined with cost savings and reliability, the 250v3 friction feeder is your best choice.

Features

Mechanical design is modular for many custom configurations

Simplified control interface software package ensures flexible and precise control

Infrared sensor for accurate count. Upgradeable to double-detect and overlap detection

Single-sided controls provide for efficient operation

Performance designed for long production runs
Patented feed separating mechanism
Closed loop system with encoder feedback

Products

Small leaflets or booklets
Small cartons
Flat cosmetics
Liquid-filled pouches
Trading cards
Business cards
Credit cards
Blister packs
Moist towelette pouches
Tax stamps
Stamps
Z-Folds
Shampoo and lotion samples
Stickers
Tickets
Coupons
Corrugated inserts
Note pads
And many more small products

Product Specs

Width: 1.96" (50mm) - 7.87" (200mm)
Length: 1.96" (50mm) - 12.8" (325mm)
Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

Typical Applications

Tipping or affixing (optional upgrade)
Batch count (optional upgrade)
Collating
Labeling
Printing, inspecting and rejecting
Integrating an Automatic Product Loader (APL)
Integrated as a base feeder to another application
Standard performance level only

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Specifications

Typical Height	31.7" (856mm)
Typical Length (ED)	25.4" (645mm)
Typical Width	21.2" (538mm)
Maximum Belt Speed	275 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.