



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation 750ip3 Friction Feeder



At a Glance

- Maximum product size: 700mm W x 400mm L (28in W x 16in L)
- Transports medium-sized to very large carton blanks, flat sheets and other products as base products quickly and efficiently
- Fast, up to 150 PPM
- Built with larger over-sized shafts for long production runs
- Ideal for tipping and affixing of large size products

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Wide-Body Feeder for Very Large Products

The MFT Automation ip3 Industrial Performance (ip) friction feeders provide superior high-performance and quality.

Standard features of the ip3 friction feeders include batch-count software and double detection. All ip3 feeders have self-contained computer/microprocessor controllers providing ease-of-use and versatility in product feeding.

Multifeeder ip3 and HCP feeders come standard with a proprietary Double Detect Sensor for true double detection to guarantee correct count. The v3 Signature Series feeders come standard with an infrared sensor to detect product overlap, and can upgrade to the Double Detect Sensor.

Designed with a powerful 750 watt one horsepower (optional 1000 watt available) brushless servo motor, computer controller, five different discharge lengths available, plus flexible and open discharge options, makes MFT friction feeders an industry leader. All of this makes our friction feeders extremely strong and robust for the most demanding applications, with the reliability to provide years of uninterrupted service.

The wide-body MFT Automation 750ip3 friction feeder transports very large, large, and medium-sized irregular carton blanks, flat sheets and other products as base products quickly and efficiently to other applications. The 750 ip3 friction feeder is designed and built with larger over-sized shafts enabling the feeder for long production runs. Tipping and affixing of large products is ideal for the 750ip3.

When very large, large, and medium-sized products need to feed at high-performance specifications,

then the 750ip3 is your best choice.

Products

Feeds all the same products as the 250, 350, and 550ip3

Very large/large/medium size flat corrugated cartons

Large posters

Large slip sheet dividers

Very large signs

Newspapers

Metal gaskets

Large pouch bags

Feed, fertilizer, concrete bags

And much more

Product Specs

Width: 0.78" (20mm) - 27.56" (700mm)

Length: 1.96" (50mm) - 12.8" (325mm)

Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

Typical Applications

High-speed feeding of very large oversized products

Batch count

Collating

Labeling

Printing, inspecting and rejecting

Integrating an Automatic Product Loader (APL)

Integrated as a base feeder to another application

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Specifications

Typical Height	38" (953mm)
Typical Length (ED)	31" (793mm)
Typical Width	41" (1037mm)
Maximum Belt Speed	100 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	205 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.