



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation Track and Trace Serialization System



At a Glance

- Turnkey product handling for serialization coding/printing
- Inspection and reject system
- Provides a trackable data file
- Highly-adaptable software package that ensures flexible and precise controls

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact and Versatile Feeder

The MFT Automation Track & Trace system offers turnkey product handling for serialization coding/printing, inspection and reject system providing a trackable data file.

An infrared sensor allows for accurate count using double-detect and overlap detection. This integrated manufacturing system is equipped with a highly-adaptable software package that ensures flexible and precise controls.

Features

Mechanical design is modular for custom configurations to meet your product needs.
Highly adaptable software package ensures for flexible and precise controls.
Infrared sensor allows for accurate count using double-detect and overlap detection.
Single-sided controls provide for efficient operation.
Easy and versatile to interface using standard industry compliant connectors.
Performance designed for long production runs.

Applications

Insertion into catch tray, box or conveyor.
Deliver a product to a secondary application.
Batching, high-speed tipping or affixing, collating systems and barcode / vision systems.

Products

Bags
Pouches
Pamphlets
Card stock products
Gift cards
Clear-film plastics
Magnets
Bandages
Carton blanks
Tyvek sheets
Pharma inserts

Product Specs

Width: 1.0" (25mm) - 11.81" (300mm)
Length: 1.0" (25mm) - 12.8" (325mm)
Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

Integration Equipment

Imaging lines
Shrink wrappers
Existing bases
Conveyers
Folder / gluer
Flow wrappers
Baggers
Case packers
Collators
Order fulfillment
Cartoners
Banders

Options

Lugged to registration stage
Reject on error
Stop on error
Guarding with safety interlock
Catch tray

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Specifications

Typical Height	31.7" (856mm)
Typical Length (ED)	25.4" (645mm)
Typical Width	21.2" (538mm)
Maximum Belt Speed	140 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.