



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# MFT Automation APL Automatic Product Loader



## At a Glance

- Multiplies capacity of your feeder
- Minimizes number of operator-assisted reloads
- Available in a variety of widths and lengths

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Consistently Feed Products to Your Friction Feeders

The MFT Automation APL Automatic Product Loader increases your production capacity by consistently loading product into your friction feeder. Maximize runtime between product reloads while minimizing the number of operators required to run the system, keeping production lines flowing.

## Better Control Irregular Products

Multifeeder APLs are also used when the shape of the product does not allow for a production stack height. Example: The top zipper end of a stand-up pouch is thicker than the bottom end of the pouch. A vertical stack of these pouches would become unstable with one end higher than the other.

Multifeeder APLs are available in a variety of widths and lengths giving you the best configuration for your application requirements.

## Benefits

**Capacity Multiplier:** Provides a larger product load capacity for longer run time between reloads.

**Feed-on-Demand:** Supplies the exact amount of product demanded by the feeder.

**Product Control:** Gives the ability to load irregular product at larger capacities than standard methods.

**Smooth Operation:** 30mm support rods and linear bearings allow the APL to be easily adjusted.

**Less Intervention:** With a larger product capacity less operator intervention and operators are required.

## Applications

Where larger capacity is required

Where the product will not stack effectively  
Where minimal operator intervention is desired

## Products

Bags  
Pouches  
Pamphlets  
Card stock  
Gift cards  
Coupons  
Magnets  
Bandages  
Carton blanks  
Tyvek sheets  
Pharma inserts

## Product Specs

Width: 1" (25mm) - 11.8" (300mm)  
Length: 1" (25mm) - 12.8" (325mm)  
Minimum Thickness: 0.003" (0.075 mm)

## Industries

Pharmaceutical  
Food  
Cosmetics  
Contract packaging  
Financial  
Printing  
Robotics

## Integration Options

Imaging lines  
Conveyers  
Poly-baggers  
Order fulfillment  
Shrink wrappers  
Folder / gluer  
Case-packers  
Collators  
Existing bases  
Flow wrappers  
Cartoners  
Banders

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

# Specifications

Typical Height	51.7" (1313mm)
Typical Length	39.7" (1000mm)
Typical Width	32.0" (812mm)
Maximum Speed	140 meters per minute
Power	110/220V 50-60Hz 6A
Operating Temp	10°-35°F (50°-95°C)

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.