



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation Hygienic APL Automatic Product Loader



At a Glance

- Multiplies capacity of your hygienic feeder
- Minimizes number of operator-assisted reloads
- Food grade safe and FDA compliant conveyor belts
- Engineered with type 304 stainless steel

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Efficient Hygienic Product Loader

The MFT Automation Hygienic APL Automatic Product Loader increases your production capacity by consistently loading pharmaceutical and food products for hygienic feeder systems in clean room environments.

Features

Engineered with type 304 stainless steel and passivated for corrosion resistance, the Hygienic APL is constructed to provide minimal contamination points, with no pits, pin holes or divots.

All MFT hygienic machines are designed for minimal disassembly with easy cleaning and maintenance, therefore reducing your risk of contamination.

Resistance to moisture and corrosion.

Food grade safe and FDA compliant conveyor belts.

APL side guides to prevent product skewing.

Small footprint with casters for easy mobility and stabilizing adjustable feet.

Electrical components are housed and protected with a sealed enclosure equivalent to NEMA rated 4X.

Applications

Handling products in processes where contamination is a risk.

Increasing product load capacity for hygienic feeder systems.

Deliver a product to another application.

Products

Pizza top sheet and cardboard
Wax slip sheets for pizzas, meat, dairy/cheese, tortillas, bakery items
Cooking bottom tray
Nutritional top sheet onto meat trays
Cardboard cooking trays
Pocket sleeves
Meat soaker pads
Coupons/promo labels
Feeding vertical fill and seal bags
Feeding cardboard for tray packing
Blood test strips
Petri test strips

Product Specs

Width: 1" (25mm) - 11.8" (300mm)
Length: 1.57" (40mm) - 12.8" (325mm)
Thickness: 0.003" (0.075 mm) - 1" (25mm)

Industries

Pharmaceutical
Food
Clean room environments

Certifications

All components are certified as IP66 or better to ensure consistent washdown performance. Meets NEMA4X standards for indoor and outdoor protection from hazardous parts, solid foreign objects, water, rain, sleet, ice, snow and corrosion.

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Specifications

Typical Height	52" (1330mm)
Typical Length	90" (2296mm)
Typical Width	29" (734mm)
Maximum Speed	NA
Power	110/220V 50-60Hz 6A
Operating Temp	2°-35°F (35°-95°C)
Operating Humidity	30 - 100

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

