



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

MFT Automation 250ip3 Friction Feeder



At a Glance

- Runs products up to 7.87in wide
- Compact and versatile feeder
- Small footprint better integrates into your production line
- Same quality and performance of the larger machines

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact and Versatile Feeder

The MFT Automation ip3 Industrial Performance (ip) friction feeders provide superior high-performance and quality.

Standard features of the ip3 friction feeders include batch-count software and double detection. All ip3 feeders have self-contained computer/microprocessor controllers providing ease-of-use and versatility in product feeding.

Multifeeder ip3 and HCP feeders come standard with a proprietary Double Detect Sensor for true double detection to guarantee correct count. The v3 Signature Series feeders come standard with an infrared sensor to detect product overlap, and can upgrade to the Double Detect Sensor.

Designed with a powerful 750 watt one horsepower (optional 1000 watt available) brushless servo motor, computer controller, five different discharge lengths available, plus flexible and open discharge options, makes Multifeeder friction feeders an industry leader. All of this makes our friction feeders extremely strong and robust for the most demanding applications, with the reliability to provide years of uninterrupted service.

The Multifeeder 250ip3 friction feeder machine is a compact and versatile machine. The small footprint enables this feeder to better integrate into your production line. The compact size of the 250ip3 feeder is an advantage for this feeder while still providing all the same quality and performance of the larger machines.

When small products are needed to feed at high-performance specifications, then the 250ip3 is your best choice.

Standard Features

Portable Unit: Self-contained unit with only one electrical enclosure

Computer Controlled: Computer control provides thousands of control calculations per second for precise start, stop, watch dog and multiple product detection

Easy Interface: Standard signals available for easy interface with existing computer, PLC or other host machinery

Production log: Automatically stores your production history in the feeder's computer with production count, and fault logging with time, date and type of fault

Intuitive User Interface: Custom 34-key sealed membrane key pad with 4 x 40 character LCD display

User-Friendly Changeover: Easy and accurate changeover with twist lock handles

Ruggedly Built: Hardened stainless steel shafts and sealed bearings for maximum life and 24-hour a day operation

Quick Belt Replacement: Three piece shaft assemblies for quick maintenance

Pre-Select Counter: Standard pre-select product count (1-999 per cycle)

Optically Isolated Signals: All interface signals isolated for accuracy

Built for Harsh Environments: Stainless steel shafts, sealed for life ball bearings, surface protected state of the art drive components and sealed durable carbon composite enclosures to protect internal parts

Software Lockout Function Option: Allows user to lock out some or all feeder functions for simplicity for the operator

Advanced Error Control: Multiple Product Detection (MPD), Watch Dog Product Jam Detection (WD-PJD), and Watch Dog No Product Detection (WD-NPD)

Typical Applications

Insertion into a catch-tray, box or conveyor

Deliver a product to a secondary application

Batching, high-speed tipping or affixing, collating systems and barcode/vision systems

Products

Small leaflets or booklets

Small cartons

Flat cosmetics

Liquid-filled pouches

Trading cards

Business cards

Credit cards

Blister packs

Moist towelette pouches

Tax stamps

Stamps

Z-Folds

Shampoo and lotion samples

Stickers

Tickets

Coupons

Corrugated inserts

Note pads

And many more small products

Product Specs

Width: 0.78" (20mm) - 7.87" (200mm)

Length: 0.78" (20mm) - 12.8" (325mm)

Thickness: 0.003" (0.075 mm) - 1" (25mm)

Industries

Pharmaceutical

Food

Cosmetics

Contract packaging

Financial

Printing

Robotics

Integration Equipment

Imaging lines

Shrink wrappers

Existing bases

Conveyers

Folder / gluer

Flow wrappers

Baggers

Case packers

Collators

Order fulfillment

Cartoners

Banders

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

Specifications

Typical Height	31.7" (856mm)
Typical Length (ED)	25.4" (645mm)
Typical Width	21.2" (538mm)
Maximum Belt Speed	275 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.