



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# MFT Automation 250v3 Friction Feeder



## At a Glance

- Maximum product width: 200mm (7.87in)
- Low-cost low-demand feeder
- Small footprint better integrates into your production line
- Same quality and performance of the larger machines

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Compact Low-Cost Feeder

The MFT Automation v3 Signature Series are economical, cost-effective friction feeders. Designed and built with the same quality as the premium ip feeders, the v3 Signature Series is engineered for lower throughput applications. With a powerful 500-watt two-thirds horsepower brushless servo motor, computer controls, and four different discharge lengths available makes the Signature Series friction feeder a top contender in its class.

The Signature Series feeders are a strong, robust and reliable lower-demand machines for simpler applications providing dependability on the production floor.

The MFT Automation 250v3 friction feeder has the same compact and versatile qualities, and feeds all the same products, as the 250ip3 friction feeder. Like the 250ip3 with its advantage in a compact size, the 250v3 feeder will also better integrate into your production line and time and cost savings will be apparent.

When small products are needed to feed and high speed is not essential, combined with cost savings and reliability, the 250v3 friction feeder is your best choice.

## Features

Mechanical design is modular for many custom configurations

Simplified control interface software package ensures flexible and precise control

Infrared sensor for accurate count. Upgradeable to double-detect and overlap detection

Single-sided controls provide for efficient operation

Performance designed for long production runs

Patented feed separating mechanism

Closed loop system with encoder feedback

## Products

Small leaflets or booklets  
Small cartons  
Flat cosmetics  
Liquid-filled pouches  
Trading cards  
Business cards  
Credit cards  
Blister packs  
Moist towelette pouches  
Tax stamps  
Stamps  
Z-Folds  
Shampoo and lotion samples  
Stickers  
Tickets  
Coupons  
Corrugated inserts  
Note pads  
And many more small products

## Product Specs

Width: 1.96" (50mm) - 7.87" (200mm)  
Length: 1.96" (50mm) - 12.8" (325mm)  
Thickness: 0.003" (0.075 mm) - 1.0" (25mm)

## Typical Applications

Tipping or affixing (optional upgrade)  
Batch count (optional upgrade)  
Collating  
Labeling  
Printing, inspecting and rejecting  
Integrating an Automatic Product Loader (APL)  
Integrated as a base feeder to another application  
Standard performance level only

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.

## Specifications

Typical Height	31.7" (856mm)
Typical Length (ED)	25.4" (645mm)
Typical Width	21.2" (538mm)
Maximum Belt Speed	275 meters per minute
Power Requirements	110/220V 50-60Hz 6amp
Operating Temp	50-95F (10-35C)
Weight Ranges	75-125 lbs
Operating Humidity	30-90%

Please [contact Pro Pac](#) or call 888-318-0083 for your friction feeding equipment.